



IRONSYSYSTEM CCT - 1000/3 CRANE FLAG/COLUMN

Reference: CCT - 1000/3

IRONSYSYSTEM CCT - 1000/3 LANDSCAPE/COLUMN CRAFT

IRONSYSYSTEM CCT - 1000/3 is a jib/column crane consisting of a 270° manually rotating jib with a maximum capacity of 1000 kg.

The cranes IRONSYSYSTEM MCT - 1000/3 are an economic, simple and practical solution, generally used to serve single workstations. In order to simplify the work between the different processing phases, it is also possible to use an overhead crane to connect the workstations and easily move the semi-finished or finished products.

IRONSYSYSTEM CCT - 1000/3 are certainly the best solution for the handling of loads, for the servicing of machine tools, for all loading and unloading operations in confined areas. These cranes are made of high quality steel. The boom is a sturdy profiled beam rotating on ball bearings. The rigid structure of the column ensures the stability of the trolley during all phases of lifting.

The cranes IRONSYSYSTEM CCT - 1000/3 respects the standard of painting is powder type RAL1004, but can also be supplied hot galvanized or treated with specific cycles for outdoor or marine environment, even highly aggressive.

The peculiarity of these plants is given by the possibility to adapt to narrow areas and limited spaces where other plants could not. Furthermore, by guaranteeing multiple configurations, they can also be installed in structures with low ceilings, with particular obstacles or with specific requirements.

TECHNICAL CHARACTERISTICS IRONSYSYSTEM CCT - 1000/3

Capacity: 1000 Kg
Reach: 3 m
Total height: 3.5 m
Underarm height: 2.650 m

COMPONENTS

- Optagonal column in bent sheet metal
- Tensioned channel arm rotating on ball bearings
- Adjustable disc brake with ferode.
- Flat cable for hoist feeding.
- Cable holder mushrooms in plastic material.
- On-Off switch.
- Powder paint finish.

Looking for a crane with different technical characteristics? [Here](#) you can find the whole range of IRONSYSYSTEM or other specialized brands

Images and technical data are not binding and may be subject to revision by the supplier.