



## QT75-560-UG-HP3 SPOTLIGHT

**UNDERWATER**

**LED**

Reference: QT75-560-UG-HP3

### QT75-560-UG-HP3 UNDERWATER LAMP

QT75-560-UG-HP3 is an underwater led spotlight for marine capable of generating a light output of 25000 lumens with borosilicate glass facade.

The QT75-560-UG-HP3 underwater spotlight was created to allow those who have an existing lighting system on their boat, to have the opportunity to make a replacement or upgrade with a new generation light without the need to change the entire system.

With up to 25000 lumens of light output and its beam angle of 90 or 120 degrees, installation requires no modification and mounting these fixtures can take as little as an hour to totally transform an existing lighting setup

Our retrofit options are fully customizable to each customer to find the item that best suits the technical features needed.

The QT75-560-UG-HP3 underwater spotlight provides for installation with Lloyd's Register, GL or ABS Design certifications. The use of the latest technology allows our QT75-560-UG-HP3 to perform well in the most challenging environment.

#### TECHNICAL FEATURES QT75-560-UG-HP3

Lumen 25000  
Kelvin: 6500  
Typical Led Life Expectancy: 40000 h  
Minimum and Maximum Operating Voltage: 110V - 240V AC  
Current/Amplifier: 1.4 - 0.7 amps  
Driver Type: External  
Driver Output: 2.8 amps @ 55V  
Control Options: On / Off Switched  
Required Removal Space: 125mm (5")  
Total Weight: 6 Kg  
Driver Dimensions (LxWxH): 220x120x90 mm  
Cable Length: 3 m

Looking for an underwater spotlight with different characteristics? [Here](#) you can find the section dedicated to nautical spotlight systems with brands specializing in the field.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

## Technical Sheet

Voltage (V)	110 - 230
Average life of LEDs (hrs)	40000
Total lumens (Lm)	25000
Weight (Kg)	6
Video	mSzY-vFJivE