



LARIUS GHIBLI 30:1 AIRLESS PUMP WITH ACCESSORIES

Reference:

LARIUS GHIBLI 30:1 AIRLESS PUMP

The pump LARIUS GHIBLI 30:1 is used for high-pressure painting without the aid of air (hence the term AIRLESS) and is capable of delivering a maximum flow rate of 3.8 l/m.

The LARIUS GHIBLI 30:1 pump is essentially made up of an air motor and a structure called "Material pumping group" or more simply "Pumping group". In the air motor, the compressed air generates the reciprocating vertical movement of the motor piston; this movement is transmitted via a connecting rod to the piston of the material pumping unit.

This causes the pump to suck in the material or push it towards the outlet. LARIUS GHIBLI 30:1 includes the transport trolley, the high-pressure material filter, the pump supply air regulator, the material suction hose (complete with filter) and the recirculation hose. The 30:1 ratio means that the material outlet pressure is 30 times the pump supply air pressure.

LARIUS GHIBLI 30:1 in the stainless steel version is particularly suitable for water-soluble coatings ("water-based coatings"). The LARIUS pump is equipped with a trolley complete with handle that allows for convenient and easy transportation.

TECHNICAL FEATURES OF THE LARIUS GHIBLI 30:1 PUMP

Maximum flow rate: 3,8 l/m
Maximum air pressure: 7 bar
Maximum pressure. operating pressure: 210 bar
Inlet air supply: 1/2" GAS (F)
Inlet: 3/4" GAS C (M)
Outlet: 3/8" GAS C (F)
Air consumption: 3 bar 400 l/m, 5 bar 800 l/m, 7 bar 850 l/m
Sound pressure level: < 80 dB (A)
Motor diameter: 180 mm (4 1/4")
Piston stroke: 102 mm (4")
c. c. Cycle: 60
N° cycles/m: 60
N° cycles/l: 16
Sealings: PTFE + Polyethylene
Weight: 25 kg
Height: 930 mm
Width: 450 mm
Depth: 450 mm

ACCESSORIES INCLUDED IN THE SUPPLY

Airless spray gun AT250 with M16x1.5 swivel connection (cod. 11200)
High pressure hose Ø 1/4" M16x1.5 mt. 7.5 (cod. 35014)

Super Fast Clean base (cod. 18270)
Super Fast Clean nozzle (cod. SFC)
Kit tools

Looking for an electric pump with different features? [Here](#) you can find the entire range of LARIUS or other specialized brands

Images and technical data are not binding. Please always consult the technical data sheet issued by the manufacturer. Manel Service accepts no liability for any changes made by the manufacturer.

Technical Sheet

Frequency (Hz)	50
Voltage (V)	230
Maximum output capacity (Lt/min)	4
Pressure (bars)	210 Max
Length (mm)	450
Width (mm)	450
Height (mm)	930
Dry weight (Kg)	25
Version	Trolley
Type of pumping group	Piston