



LARIUS NOVA 68:1 INOX AIRLESS PUMP

Reference:

LARIUS NOVA 68:1 AIRLESS PUMP

The pump LARIUS NOVA 68:1 pneumatic is used for high-pressure coating without the aid of air (hence the term AIRLESS) and is capable of delivering a maximum flow rate of 10 l/m.

LARIUS NOVA 68:1 is a high-performance pump that combines both high flow rates and the ability to spray very heavy products such as intumescent, tar, rustproofing, etc.

LARIUS NOVA 68:1 pumps are made to be used in difficult situations such as carpentry, shipyards and industries, where very reliable and professional equipment is needed.

In contrast to air-assisted systems, airless systems spray material under pressure without the support of air. LARIUS NOVA 68:1 is a pneumatically driven pump, it puts the material under pressure by delivering a certain amount of material at 7 bar through the nozzle hole forming an atomized jet.

The LARIUS NOVA 68:1 pump is equipped with a trolley with a handle that allows a comfortable and easy transport, it is also supplied with a high pressure filter, the air supply regulator of the pump, the suction pipe (complete with filter) and the recirculation pipe. The 68:1 ratio means that the material output pressure is 68 times the air pressure of the pump supply.

The LARIUS NOVA 68:1 pump is supplied complete with:

- NOVA 68:1 pump body
- Trolley
- High pressure hose 3/8" mt 15
- High pressure hose 1/4" mt 1,5
- LX91 gun with swivel connection
- Nozzle base + FAST CLEAN nozzle (23-40)

TECHNICAL FEATURES LARIUS NOVA 68:1 PUMP

Maximum flow rate: 11 l/min
Maximum air pressure: 6.5 bar - 94 psi
Maximum fluid pressure: 450 bar - 6525 psi
Flow rate per cycle: 180 cc
Air inlet: 1" BSPP (F)
Material inlet: 1" NPSM (M)
Material outlet: 3/8" NPSM (M)
Sound level pressure: < 90 db (A)
Effective motor diameter: 254 mm (10")
Piston stroke: 120 mm (4 3/4")

Gasket material: PTFE, Polyethylene
Weight: 112 Kg

Looking for an electric pump with different features? [Here](#) you can find the full range of LARIUS or other specialized brands

Images and technical data are not binding and may be subject to revision by the supplier.

Technical Sheet

Maximum output capacity (Lt/min)	10
Pressure (bars)	408 Max
Acoustic pressure	90 dB (A)
Height (mm)	1110
Dry weight (Kg)	112
Version	Trolley
Type of pumping group	Piston