



## LARIUS DRAGON LINER 4600 ROAD MARKER

Reference: 4600

## LARIUS DRAGON LINER 4600 ROAD TRACKER

LARIUS DRAGON LINER 4600 is an airless road tracer equipped with a Yamaha gasoline engine, capable of delivering a maximum power of 9 Hp.

LARIUS DRAGON LINER 4600 is referred to as a "piston pump." A piston pump is a device used for high-pressure painting without the aid of air (hence the term "airless").

The pump is a device used for high-pressure painting without the aid of air (hence the term "airless").

The internal combustion engine, mounted on board the LARIUS DRAGON LINER 4600, drives the reciprocating pump. An eccentric shaft and connecting rod provide the reciprocating motion necessary to operate the piston of the "pumping unit". The movement of the piston creates a vacuum.

The product is sucked in, pushed towards the outlet of the LARIUS DRAGON LINER 4600 and sent through the high pressure hose to the gun. An electronic device allows to regulate and control the pressure of the material coming out of the pump. A safety valve against overpressure guarantees the absolute reliability of the equipment.

LARIUS DRAGON LINER 4600 uses non-pre-mixed coatings, which allows for a yield that is approximately 30% higher than that of standard tracing. Each model is also an airless sprayer that can be used in the construction industry with washable products, enamels, transpirants and resins for flooring. A wide range of accessories is available to meet the tracer's equipment requirements.

Each model is complete with:

- Filter with manometer;
- 1 high pressure hose Ø 1/4" M16x1. 5 of 15 m;
- 1 Piston stroke compensator;
- 1 Suction / recirculation system
- 2 AT260 airless hand gun;
- 2 Super Fast Clean Base
- Super Fast Clean Base 2 x 13-40 / 2 x 17-40 / 2 x 21-40
- 1 flashing light pole;
- 1 Speed control panel
- Case with tools

### TECHNICAL CHARACTERISTICS LARIUS DRAGON LINER 4600

Combustion engine power: 9 Hp  
Max flow rate: 7 l/min  
Fuel supply: Petrol

Engine: Yamaha  
Max pressure: 230 bar  
Airless nozzle: No. 2 AT 250  
Power supply: 24 V  
Supplied nozzle sizes: 2 x 13x40 - 2 x 17x40 - 2 x 21x40 - 1 x 19-40  
Colors: 1  
Treatment: manual  
Applications: Large road maintenance plotting jobs  
Multipurpose sprayer: standard  
Vibrations  $L_{eq(8h)} = 1.5 \text{ m/s}^2$   
Length: 1650 mm  
Height: 1000 mm  
Width: 750 mm  
Weight: 220 kg

Are you looking for a road marker with different characteristics? [Here](#) you can find the full range of LARIUS or other brands specializing in this field.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

## Technical Sheet

Fuel	Gasoline
Pressure (bars)	230
Length (mm)	1650
Width (mm)	750
Height (mm)	1000
Dry weight (Kg)	220
Drive	Manual
Maximum paint flow rate (Lt/min)	7
Number paint colors	1
Number of guns supported	2
Engine manufacturer	Yamaha
Video	DqK_vK5tqWo