

Le immagini riportate sono indicative



MOSA GE SX-11000 KDT

Reference: CM4S00F1

MOSA GE SX-11000 KDT 8,8 KW Supersilenced Generator AVR

MOSA GE SX-11000 KDT is a single-phase and three-phase 8,8 KW diesel-powered generator set, with Kohler engine, supersilenced and with AVR technology voltage regulator. The MOSA GE SX-11000 KDT is easy to transport thanks to the central lifting hook and has a sealed basement that can contain any leaks of liquids in the engine, thus avoiding environmental pollution.

Even quieter and more efficient than traditional models, the MOSA GE SX-11000 KDT genset delivers a stable and precise three-phase power of 8.8 KW, suitable for powering sophisticated electronic equipment that is sensitive to voltage and frequency variations.

You can therefore quietly and easily enjoy all the little comforts of home wherever you are: lights, fans, a coffee machine, laptops, radio or TV.

The MOSA GE SX-11000 KDT genset is equipped with a 38 litre capacity tank for up to almost 15 hours of continuous operation at 75% load.

The control panel of the MOSA GE SX-11000 KDT genset houses the machine's sockets and controls, including the differential switch, circuit breaker and thermal protection.

A TCM remote control is also available for the MOSA GE SX-11000 KDT genset (on request), which allows the engine to be started/stop up to 10 metres away from the machine.

The MOSA GE SX-11000 KDT genset is suitable for a wide range of uses such as construction, equipment rental, events.

Technical features of the MOSA GE SX-11000 KDT:

Three-phase maximum power: 11 KVA

Three-phase continuous use power: 10 KVA

Maximum power three-phase: 8.8 KW

Three phase continuous use power: 8 KW

Single-phase continuous use power: 6 KVA

Single-phase continuous use power: 6 KW

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Engine: Kohler KDW702

Starting: Electric

Consumption: 2.6 Lt/h at 75% of the load

Length: 1568 mm

Width: 710 mm

Height: 1115 mm

Weight: 340 Kg

Supersilenced

AVR

Tank capacity: 38lt

Stage 5

If you are looking for another product such as MOSA GE SX-11000 KDT generator set then you can browse our catalog for more [overland generator sets](#).

Images and technical data are not binding.

Technical Sheet

Phase	Single phase / Three phase
Continuous power single phase (KW)	6
Continuous power single phase (KVA)	6
Maximum power three phase (KW)	8.8
Continuous power three phase (KW)	8
Maximum power three phase (KVA)	11
Continuous power three phase (KVA)	10
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 400V 16A 3P+N+T CEE IP67 - 2 x 230V 16A 2P+T CEE IP67 - 1 x 230V 16A 2P+T Schuko
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Speed governor	Mechanical
Starting system	Elettrico
Engine capacity (cm ³)	686
Number cylinders	2
Oil capacity (L)	1.6
Cooling	Water
Alternator	Synchronous self-excited, self-regulated
Fuel tank capacity (L)	38
Consumption (L/h)	2.6
Running time (h)	14.5
Acoustic power	93 dB(A)
Acoustic pressure	68 dB(A) at 7 m
Length (mm)	1568
Width (mm)	710
Height (mm)	1115

Dry weight (Kg)	340
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Kohler
