



MOSA GE 14000 SXC/GS EAS USED

Reference: USATO 9

Technical Sheet

Phase	Single phase / Three phase
Continuous power single phase (KW)	4
Continuous power single phase (KVA)	5
Maximum power three phase (KW)	12
Continuous power three phase (KW)	10.8
Maximum power three phase (KVA)	15
Continuous power three phase (KVA)	13.5
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V 16A
Engine	Lombardini 12LD477/2
Engine rpm (rpm)	3000
Starting system	Electric
Engine capacity (cm ³)	954
Number cylinders	2
Cooling	Air
Inyección	Direct
Alternator	Sincrono trifase, autoeccitato, autoregolato
Fuel tank capacity (L)	23

Running time (h)	8.2 at 75% of the load
Acoustic power	96 dB(A)
Acoustic pressure	71 dB(A) at 7 m
Length (mm)	1320
Width (mm)	790
Height (mm)	750
Dry weight (Kg)	315
Silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	Compound
Engine manufacturer	Lombardini