



MASE IS 34.06 K MARINE GENERATOR SINGLE-PHASE 34KW EPA

Reference: MASE IS 34.06 K

MASE IS 34.06 K MARINE GENERATOR SINGLE-PHASE 34KW EPA

MASE IS34,06K single-phase marine generator with KUBOTA V3300 engine with diesel power supply at 1800 rpm capable of delivering a power of 34KW.

The MASE IS34,06K marine generator is designed with a soundproof cabin that makes it **supersilenced**. The MASE IS34,06K is built with Kubota diesel-powered engine and synchronous alternator, self-excited with air/water cooling. With its small size, it is also suitable on small boats.

The marine generator CBU control module has a new design, the latest technology, a large display and micro-buttons for quick navigation of menus, start and stop procedures; IP54 protection rating. Very compact, 86x124mm and equipped with 10mts shielded cable, the CBU module has multiple functions for complete monitoring of the MASE IS34,06K.

The soundproof cabin of the MASE IS34,06K is constituted by a bearing structure in aluminum profile that supports panels in marine aluminum painted type 5754 extremely light and of high resistance to the external agents. The excellent accessibility to the internal compartment makes maintenance easier even with the generator set installed in narrow spaces.

The MASE IS34,06K marine generator has **EPA certification** valid only for the **U.S. market**

Technical Features:

Phase Type: Single Phase
Maximum Power: 34KW
Fuel: Diesel
Voltage: 120 / 240 V
Frequency: 60 Hz
Engine: KUBOTA V3300, 4 Stroke
Length: 1260 mm
Width: 640 mm
Height: 830 mm
Weight: 630 Kg

If you are looking for another generator as the MASE IS34,06K then you can see the entire catalog of [marine generators](#).

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	34
Fuel	Diesel
Frequency (Hz)	60
Voltage (V)	120 / 240
Engine	KUBOTA V3300-BG
Engine rpm (rpm)	1800
Speed governor	Electronic
Engine capacity (cm ³)	3318
Number cylinders	4
Cooling	Air / water (Intercooler W/A)
Inyección	Indirect
Alternator	Synchronous, self-excited
Poles	4
Lubrication	Forced
Consumption (L/h)	13 at 100% of the load
Acoustic pressure	54 dB(A) at 7 m
Length (mm)	1260
Width (mm)	640
Height (mm)	830
Dry weight (Kg)	630
Inverter	No
AVR	Yes
Compound	No
Silenced	Yes
Super silenced	Yes