



MARINE GENERATOR MASE IS 25 T - THREE-PHASE 28KVA

Reference: MASE IS 25 T

MASE IS 25 T THREE PHASE MARINE GENERATOR 28KVA

MARINE GENERATOR MASE IS25T three-phase marine generator with Yanmar 4TNV84 engine with diesel power supply at 1500 rpm capable of delivering a power of 28KVA.

The MASE IS25T marine generator is designed with a soundproof cabin that makes it **supersilenced**. The MASE IS25T marine generator is built with a Yanmar diesel-powered engine and synchronous alternator, self-excited with air/water cooling. With its small size, it is also suitable on small boats.

The marine generator CBU control module has a new design, the latest technology, a large display and micro-buttons for quick navigation of menus, start and stop procedures; IP54 protection rating. Very compact, 86x124mm and equipped with 10mts shielded cable, the CBU module has multiple functions for complete monitoring of the MASE IS25T.

The soundproof cabin of the MASE IS25T consists of a load-bearing structure in aluminum profile that supports panels in marine aluminum painted type 5754 extremely light and very high resistance to external agents. The excellent accessibility to the internal compartment makes maintenance easier even with the genset installed in narrow spaces.

Technical Features:

Maximum Power: 28KVA
Fuel: Diesel
Voltage: 400 V
Frequency: 50 Hz
Engine: Yanmar 4TNV84, 4 Strokes
Length: 1225 mm
Width: 630 mm
Height: 830 mm
Weight: 625 Kg

If you are looking for another generator as the MASE IS25T then you can see the entire catalog of [marine generators](#).

Images and technical data are not binding.

Technical Sheet

Phase

Three phase

| | |
|------------------------------------|-------------------------------|
| Maximum power three phase (KVA) | 28 |
| Fuel | Diesel |
| Frequency (Hz) | 50 |
| Voltage (V) | 400 |
| Engine | Yanmar 4TNV84 TURBO, 4 stroke |
| Engine rpm (rpm) | 1500 |
| Speed governor | Centrifugal, mechanical |
| Engine capacity (cm ³) | 3319 |
| Number cylinders | 4 |
| Cooling | Air / water (Intercooler W/A) |
| Inyección | Direct |
| Alternator | Synchronous, self-excited |
| Poles | 4 |
| Lubrication | Forced |
| Consumption (L/h) | 8.9 |
| Acoustic pressure | 53 dB(A) at 7 m |
| Length (mm) | 1225 |
| Width (mm) | 630 |
| Height (mm) | 830 |
| Dry weight (Kg) | 625 |
| Inverter | No |
| AVR | Yes |
| Compound | No |
| Silenced | Yes |
| Super silenced | Yes |
| Product type | Generator |
| Voltage regulator | AVR |
| Engine manufacturer | Yanmar |