



MASE MARINER 906 S SINGLE PHASE MARINE GENERATOR SILENCED 9KW EPA

Reference: MARINER 906 S EPA

MASE MARINER 906 S SILENCED SINGLE-PHASE MARINE GENERATOR 9KW EPA

MASE MARINER906S single-phase silenced marine generator is equipped with a YANMAR 3TNV80F engine with **EPA emissions standard**, powered by diesel and capable of delivering a maximum power of 9 KW at 1800 rpm.

The MASE MARINER906S is built with and synchronous alternator, self-excited with air cooling, is extremely compact and powerful, suitable even on small boats. The alternator is complete with a voltage regulator that ensures the stability of the voltage delivered by the generator, delivering current like at home.

The MASE MARINER906S allows easy access for maintenance of the fuel and lubrication systems, sea water pump, air filter, oil filter and fuel. It is also equipped with safety systems of auto stop for low oil pressure and high temperature engine or exhaust gas.

The MASE MARINER906S is equipped with a soundproof cabin that makes it super silent, with a sound emission of 53dB(A) at a distance of 7 m. The painted aluminum soundproofing cabin is extremely lightweight and of very high resistance to external agents.

The MASE MARINER906S marine generator has **EPA certification** valid only **for the US market**.

TECHNICAL FEATURES MASE MARINER906S

Phase Type: Single Phase
Maximum Power: 9 KW
Fuel: Diesel
Voltage: 120 - 240 V
Frequency: 60 Hz
Engine: YANMAR 3TNV80F, 4 Stroke
Emission Standard: EPA
Mechanical Power: 14.35 Hp
Number of cylinders: 3
Displacement: 1267 cc
Engine RPM: 1800 rpm
Fuel consumption: 3.1 l/h
Sound pressure: 53 dB(A) @ 7 m
Alternator: Synchronous Brushless
Voltage regulator: Yes
Length: 921 mm
Width: 581 mm
Height: 656 mm
Weight: 295 Kg

If you are looking for another marine generator then you can browse the entire catalog of [marine generators](#).

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	9
Fuel	Diesel
Frequency (Hz)	60
Voltage (V)	120 / 240
Engine	YANMAR 3TNV80F
Emissions Regulations	EPA
Engine rpm (rpm)	1800
Speed governor	Centrifugal, mechanical
Engine capacity (cm ³)	1267
Number cylinders	3
Cooling	Air
Inyección	Direct
Alternator	Synchronous, self-excited
Poles	4
Lubrication	Forced
Consumption (L/h)	3.1 at 100% of the load
Acoustic pressure	53 dB(A) at 7 m
Length (mm)	921
Width (mm)	581
Height (mm)	656
Dry weight (Kg)	295
Inverter	No
AVR	No
Compound	No
Silenced	Yes
Super silenced	Yes
Voltage regulator	YES