



## MASE MARINER 2460 KS SINGLE PHASE MARINE GENERATOR SILENCED 24KW EPA

Reference: MARINER 2460 KS EPA

### MASE MARINER 2460 KS SILENCED SINGLE-PHASE MARINE GENERATOR 24 KW EPA

MASE MARINER2460KS single-phase silenced marine generator is equipped with a KUBOTA V2403 Diesel engine with **EPA emissions standard**, capable of delivering a maximum power of 24 KW at 1800 rpm.

The MASE MARINER2460KS alternator is a 4-pole synchronous, self-regulated, self-excited, brushless alternator, which in combination with the powerful KUBOTA engine can deliver a maximum power of 24 KW. The alternator is complete with AVR voltage regulator that ensures the stability of the voltage delivered by the generator, delivering current like the one at home.

The MASE MARINER2460KS allows easy access for maintenance of the alimentation and lubrication systems, seawater pump, air filter, oil filter and fuel. It is also equipped with safety systems of auto stop for low oil pressure and high temperature engine or exhaust gas.

The MASE MARINER2460KS is equipped with a soundproof cabin that makes it super silent, with a sound emission of 51dB(A) at a distance of 7 m. The painted aluminum soundproofing cabin is extremely lightweight and of very high resistance to external agents.

The MASE MARINER2460KS marine generator has **EPA certification** valid only **for the US market**.

#### TECHNICAL FEATURES MASE MARINER2460KS

Phase Type: Single Phase  
Maximum Power: 24 KW  
Fuel: Diesel  
Voltage: 120 - 240 V  
Frequency: 60 Hz  
Engine: KUBOTA V2403, 4 Stroke  
Emissions Standard: EPA  
Mechanical Power: 39.8 Hp  
Number of cylinders: 4  
Displacement: 2434 cc  
Engine RPM: 1800 rpm  
Fuel consumption: 6.5 l/h  
Sound pressure: 51 dB(A) @ 7 m  
Alternator: Synchronous Brushless  
Voltage regulator: AVR  
Length: 1135 mm  
Width: 631 mm  
Height: 694 mm  
Weight: 465 Kg

If you are looking for another marine generator then you can browse the entire catalog of [marine generators](#).

Images and technical data are not binding.

## Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	24
Fuel	Diesel
Frequency (Hz)	60
Voltage (V)	120 / 240
Engine	KUBOTA V2403
Emissions Regulations	EPA
Engine rpm (rpm)	1800
Speed governor	Electronic
Engine capacity (cm <sup>3</sup> )	2434
Number cylinders	4
Cooling	Air
Inyección	Indirect
Alternator	Synchronous, self-excited
Poles	4
Lubrication	Forced
Consumption (L/h)	6.5
Acoustic pressure	51 dB(A) at 7 m
Length (mm)	1135
Width (mm)	631
Height (mm)	694
Dry weight (Kg)	465
Inverter	No
AVR	Yes
Compound	No
Silenced	Yes
Super silenced	Yes
Voltage regulator	AVR