



ITALTOWER TOWERLOOP PRO02 LIGHT TOWER 4x75W MULTILED

Reference: TWLOOP_PRO02

ITALTOWER TOWERLOOP PRO02 LIGHT TOWER 4x75W MULTILED

ITALTOWER TOWERLOOP PRO02 is a light tower equipped with 4 led projectors 75W high brightness with directional optics and handles for easy rotation, with a lifting system that allows an extension up to 7 mt.

The ITALTOWER TOWERLOOP PRO02 light tower is supplied with a plug socket kit for the connection in series of several units up to a maximum of 6. The ITALTOWER TOWERLOOP PRO02 is supplied with galvanized guides and eyebolts for moving and lifting. These features make the operation by the operator very simple, making the unit easy to handle and use.

The efficient manual lifting system is able to bring the projectors to a height of 7 m, combined with 4 LED lamps, the light tower can illuminate an area of 2000 square meters with a maximum luminous intensity of 36900 lm.

The ITALTOWER TOWERLOOP PRO02 is equipped with 4 stabilizers which make the light tower resistant to strong wind gusts up to 100 km/h. ITALTOWER TOWERLOOP PRO02 is NOT equipped with an internal generator, but in return it can be effectively powered by an external source such as a generator set or can be connected directly to the power grid.

ITALTOWER TOWERLOOP PRO02 TECHNICAL FEATURES

Number of luminaires: 4
Lamp wattage: 75 W multiLED
Lumen: 36900 lm
Illuminated area: 2000 square metres
Phase type: Single phase
Voltage: 110 / 230 V
Frequency: 50 Hz (60 Hz ONLY ON REQUEST)
Output: 230 V 16A
Maximum height: 7 m
Lifting system: Manual
Rotation: 359°
Wind resistance: 100 Km/h
Trolley: Hand-drawn trolley
Stabilisers: 4
Length (mm): min 930 - MAX 1800
Width (mm): min 800 - MAX 1600
Height (mm): min 2300 - Max 7000
Dry weight (Kg): 235

Are you looking for a light tower with different characteristics? [Here](#) you can find the full range of light towers ITALTOWER or other specialized brands.

Images and technical data are not binding and may be subject to revision by the supplier.

Technical Sheet

Phase	Single phase
Frequency (Hz)	50
Voltage (V)	110 / 230
Type of lamps	MULTILED
Lamps	4 x 75 W
Telescopic pole	Vertical
Illuminated area (m ²)	2000
Lifting System	Manual lifting system
Maximum height (m)	7
Mast rotation	359°
Open size (mm)	
Length closed (mm)	930
Width closed (mm)	800
Height closed (mm)	2300
With generator / Without generator	Without generator
Transportability	Stationary
Stability to wind (Km/h)	100 Km/h
Weight (Kg)	235