

MARINE GENERATOR SUPERSILENCED AVR 22 KVA SINGLE PHASE

Reference: MA22KVAM



These generator sets for the nautical sector are a reference point on the market for the optimal relationship between performance, silence and reduced dimensions.

Silent

Both the engine and the Paguro generator alternator are water cooled: as no ventilation is required for cooling, noise is drastically reduced.

In addition, the outer shell has a single small opening for the entry of combustion air with a labyrinth path that prevents the exit of noise, the outer shell is made of reinforced fiberglass multilayer and covered with high-density neoprene for maximum sound insulation.

Lightweight and compact

The built with ad hoc components to reduce the overall dimensions and exploit the empty spaces inside.

Safe

The generators equipped with alarm indicators and a charging indicator with LED light for an immediate evaluation of the power delivered. They stop automatically in the event of low oil pressure or overtemperature.

Non-binding images and technical data.

Technical Sheet

Phase	Single phase
Continuous power single phase (KW)	22
Continuous power single phase (KVA)	22
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Engine	Kohler KDI 2504 M
Engine rpm (rpm)	1500
Starting system	Electric

Number cylinders	4
Cooling	Water
Alternator	Brushless
Acoustic pressure	53 dB(A)
Length (mm)	1224
Width (mm)	710
Height (mm)	828
Dry weight (Kg)	620
Silenced	Yes
Super silenced	Yes
Product type	Generator
Voltage regulator	AVR
Engine manufacturer	Kohler