



MOSA GE 8000 KBT SINGLE-PHASE/THREE-PHASE GENERATOR 8KVA STAGE V

Reference: CK2S9000

MOSA GE 8000 KBT THREE-PHASE GENERATOR 8KVA STAGE V

MOSA GE8000 KBT is a single-phase/three-phase generator with KOHLER CH 440 Stage V powered by gasoline, capable of delivering a maximum power of 8 KVA.

MOSA is compact and convenient to maneuver and transport thanks to its compact size, its weight of 82 kg, equipped with practical tubular handles.

The MOSA GE8000 KBT is certified for Stage V European emission standards, this allows the handling of the generator.

The MOSA GE8000 KBT generator set is equipped with manual recoil start. The alternator of the MOSA GE8000 KBT generator set is synchronous, single-phase, self-excited, self-regulated, brushless and with class H insulation.

The control panel is equipped with a manual recoil starter.

The control panel is composed of:

- Output sockets: 1x400V 16A 3P+N +T CEE / 1x230V 16A 2P+T CEE
- Motor switch ON-OFF
- Air control
- Voltmeter
- Thermomagnetic circuit breaker
- Earth terminal (PE)

Technical specifications MOSA GE8000 KBT :

Phase Type: SinglePhase/ThreePhase
Maximum ThreePhase Output: 8 KVA
Continuous ThreePhase Output: 7 KVA
Maximum ThreePhase Output: 6.4 KW
Continuous ThreePhase Output: 5.6 KW
Continuous Single-phase Power: 4 KVA
Continuous Single-phase Power: 3.2 KVA
Fuel: Gasoline
Voltage: 230 - 400 V
Frequency: 50 Hz
Motor: KOHLER CH 440 COMMAND PRO
Emission Standard: Stage V
Number of cylinders: 1
Displacement: 429 cc
Engine speed: 3000 rpm

Tank capacity: 7 l
 Acoustic pressure: 74 dB(A) @ 7 m
 Alternator: Synchronous Brushless
 Length: 770 mm
 Width: 520 mm
 Height: 650 mm
 Weight: 82 Kg

If you are looking for another product like the MOSA GE8000 KBT generator set then you can check out our catalog for other [land based generator sets](#).

Images and technical data are not binding.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	3.2
Maximum power single phase (KVA)	4
Maximum power three phase (KW)	6.4
Continuous power three phase (KW)	5.6
Maximum power three phase (KVA)	8
Continuous power three phase (KVA)	7
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1x400V 16A 3P+N +T CEE / 1x230V 16A 2P+T CEE
Engine	
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Speed governor	Mechanical
Ignition	Recoil
Starting system	Pull starter
Engine capacity (cm ³)	429
Number cylinders	1
Cooling	Air
Alternator	Synchronous self-excited, self-regulated, brushless
Bore x stroke (mm)	89 x69
Length (mm)	770
Width (mm)	520
Height (mm)	650

Dry weight (Kg)	82
Silenced	No
Compression ratio	
ATS Switch device	No ATS
Voltage regulator	No
Engine manufacturer	Kohler
