



## VARMATEC TANDEM 550/15 WATERPROOF INFRARED HEATER 1500W

Reference: 550/15

### VARMATEC TANDEM 550/15 WATERPROOF INFRARED HEATER 1500W

VARMATEC TANDEM 550/15 is an infrared heater 1500W for both indoor and outdoor applications, perfectly insulated and Waterproof does not fear rain and splashing water.

VARMATEC TANDEM 550/15 is an extremely versatile infrared heater. It can be used in different situations and above all it can be a valid caloric support in all your activities. Its heat is immediate and consumes little electricity, it occupies little space but has the characteristic of heating a very large space.

VARMATEC TANDEM 550/15 has been designed and built with a technique and assembled with the best components complying with the regulations and/or certified for the safeguard of the safety in the use.

VARMATEC TANDEM 550/15 can be supplied in two colors, and included in the supply will be provided all the necessary for the wall or ceiling installation.

VARMATEC TANDEM 550/15 has been projected to be used in single or in coupling, horizontal or vertical, so as to allow, if necessary, a greater heating intensity.

#### TECHNICAL FEATURES VARMATEC TANDEM 550/15

Power: 1500 W  
Power supply voltage: 220 - 240 V  
Power supply frequency: 50 - 60 Hz  
Heated area: 15 / 20 m<sup>2</sup>  
Structure : Die-cast aluminum  
Protection class: IPX5 Waterproof  
Fixing: Wall or Ceiling  
Recommended Installation Height: 2.5 - 2.8 m  
Bulb Color: Gold  
Cable Length: 1.5 m  
Length: 460 mm  
Depth: 190 mm  
Height: 85 mm  
Net Weight: 3 Kg

Looking for a product with different technical characteristics? [Here](#) you can the section dedicated to professional heaters and heaters VARMATEC or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

## Technical Sheet

Frequency (Hz)	50 / 60
Voltage (V)	220 - 240
Power (KW)	1.5
Protection degree	IPX5 Waterproof
Power cable length (m)	1.5
Length (mm)	460
Width (mm)	190
Height (mm)	85
Dry weight (Kg)	3