



## CGM 20P-B20 WITH AUTOMATIC CONTROL PANEL

Reference: CGM 20P-B20 AUTOMATICO

### CGM 20P-B20 Single/three-phase 20KVA generator with automatic control panel

The CGM 20P-B20 is a single/three phase 20KVA generator with a 1500 rpm Perkins diesel engine, compact and easy to use, mounted on a fixed base. This CGM 20P-B20 generator is in an open version and is easy to handle and transport thanks to its base with pivoting feet.

The CGM 20P-B20 generator consists of a Linz, Stamford or Mecc Alte, self-excited, brushless alternator with AVR voltage regulator. The CGM 20P-B20 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 4 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use. In addition, it is equipped with a panel with an automatic control unit and terminal block for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 20P-B20 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

#### Technical characteristics of the CGM 20P-B20 generator:

Tipo di fase: Monofase / Trifase

Potenza massima trifase: 17.6 KW / 22 KVA

Potenza uso continuo trifase: 16 KW / 20 KVA

Potenza massima monofase: 5.87 KW / 7.33 KVA

Potenza uso continuo monofase: 5.33 KW / 6.67 KVA

Carburante: Diesel

Tensione: 230 V / 400 V

Frequenza: 50 Hz

Motore: PERKINS 404A-22G1

Giri motore: 1500 giri/min

Avviamento: Elettrico

Consumo: 4 Lt/h al 75% del carico

Lunghezza: 1400 mm

Larghezza: 700 mm

Altezza: 1400 mm

Peso: 495 Kg

AVR

If you are looking for a product like the CGM 20P-B20 then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Phase	Single phase / Three phase
Maximum power single phase (KW)	5.8
Continuous power single phase (KW)	5.33
Maximum power single phase (KVA)	7.3
Continuous power single phase (KVA)	6.67
Maximum power three phase (KW)	17.6
Continuous power three phase (KW)	16
Maximum power three phase (KVA)	22
Continuous power three phase (KVA)	20
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	Morsettiera
Engine	Perkins 404A-22G1
Emissions Regulations	Stationary Use
Engine rpm (rpm)	1500
Speed governor	Mechanical
Starting system	Elettrico
Engine capacity (cm <sup>3</sup> )	2216
Number cylinders	4
Cooling	Water
Alternator	Brushless
Poles	4
Protection degree	IP44
Bore x stroke (mm)	84 x 100
Fuel tank capacity (L)	55
Consumption (L/h)	4
Running time (h)	27.5
Length (mm)	1400
Width (mm)	700
Height (mm)	
Dry weight (Kg)	495
AVR	Yes
Silenced	No
Super silenced	No

---

Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Perkins

---