



CGM 500P-C500 WITH MANUAL CONTROL PANEL

Reference: CGM 500P-C500 MANUALE

CGM 500P-C500 Single/three-phase 500KVA generator super-silenced with manual control panel

The CGM 500P-C500 is a single/three phase 500KVA generator with a 1500 rpm Perkins diesel engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproofed cabin made of structural steel plate, weatherproofing and an interior lining made of soundproofing material with high noise reduction, which makes the CGM 500P-C500 supersilenced. The CGM 500P-C500 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 500P-C500 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 76 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 500P-C500 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 500P-C500 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 440 KW / 550 KVA

Three-phase continuous power: 400 KW / 500 KVA

Maximum single-phase power: 146.67 KW / 183.33 KVA

Single-phase continuous use power: 133.33 KW / 166.67 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: PERKINS 2506A-E15TAG2

Engine speed: 1500 rpm

Starting: Electric

Consumption: 76 Lt/h at 75% load

Length: 4850 mm

Width: 1850 mm

Height: 2550 mm

Weight: 5140 Kg

Super-silenced

AVR

If you are looking for a product like the CGM 500P-C500 then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	146.67
Continuous power single phase (KW)	133.33
Maximum power single phase (KVA)	183.33
Continuous power single phase (KVA)	166.67
Maximum power three phase (KW)	440
Continuous power three phase (KW)	400
Maximum power three phase (KVA)	550
Continuous power three phase (KVA)	500
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	Morsettiera
Engine	Perkins 2506A-E15TAG2
Emissions Regulations	Stationary Use
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Elettrico
Engine capacity (cm ³)	15200
Number cylinders	6
Cooling	Water
Alternator	Brushless
Poles	4
Protection degree	IP44
Bore x stroke (mm)	137 x 171
Fuel tank capacity (L)	400
Consumption (L/h)	76
Running time (h)	15
Acoustic pressure	69 dB(A) at 7 m
Length (mm)	4850
Width (mm)	1850
Height (mm)	2550
Dry weight (Kg)	5140

Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	Perkins
