



CGM 120F-B100 WITH MANUAL CONTROL PANEL

Reference: CGM 120F-B100 MANUALE

CGM 120F-B100 Single/three-phase 120KVA generator with manual control panel

The CGM 120F-B100 is a single/three phase 120KVA generator with a 1500 rpm FPT diesel engine, compact and easy to use, mounted on a fixed base. This CGM 120F-B100 generator is in an open version and is easy to handle and transport thanks to its base with pivoting feet.

The CGM 120F-B100 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 120F-B100 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 21 litres per hour at 75% load. The fuel tank is incorporated in the crankcase for ease of use.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 120F-B100 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 120F-B100 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 105.6 KW / 132 KVA

Three-phase continuous power: 96 KW / 120 KVA

Maximum single-phase power: 35.2 KW / 44 KVA

Single-phase continuous use power: 32 KW / 40 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: FPT NEF N45TM3

Engine speed: 1500 rpm

Starting: Electric

Consumption: 21 Lt/h at 75% load

Length: 2100 mm

Width: 1000 mm

Height: 1800 mm

Weight: 1245 Kg

AVR

If you are looking for a product like the CGM 120F-B100 then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	35.2
Continuous power single phase (KW)	32
Maximum power single phase (KVA)	44
Continuous power single phase (KVA)	40
Maximum power three phase (KW)	105.6
Continuous power three phase (KW)	96
Maximum power three phase (KVA)	132
Continuous power three phase (KVA)	120
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	Morsettiera
Engine	FPT (IVECO) NEFN45TM3
Emissions Regulations	Stationary Use
Engine rpm (rpm)	1500
Speed governor	Mechanical
Starting system	Elettrico
Engine capacity (cm ³)	4500
Number cylinders	4
Cooling	Water
Alternator	Brushless
Poles	4
Protection degree	IP44
Bore x stroke (mm)	104 x 132
Fuel tank capacity (L)	120
Consumption (L/h)	21
Running time (h)	5.7
Length (mm)	2100
Width (mm)	1000
Height (mm)	
Dry weight (Kg)	1245
AVR	Yes
Silenced	No
Super silenced	No

Product type	Generator
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	FPT Iveco
