



CGM 150F-C200 WITH AUTOMATIC CONTROL PANEL

Reference: CGM 150F-C200 AUTOMATICO

CGM 150F-C200 Single/three-phase 150KVA generator with automatic control panel

The CGM 150F-C200 is a single/three phase 150KVA generator with a 1500 rpm FPT diesel engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproofed cabin made of structural steel plate, weatherproofed and lined with sound-absorbing material with high noise reduction, making the CGM 150F-C200 super-silenced.

The CGM 150F-C200 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 150F-C200 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 26 litres per hour at 75% load. In addition, it has a control panel with automatic control unit and terminal box for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 150F-C200 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 150F-C200 generator:

Phase type: Single-phase / Three-phase
Maximum three-phase power: 132 KW / 165 KVA
Three-phase continuous power: 120 KW / 150 KVA
Maximum single-phase power: 44 KW / 55 KVA
Single-phase continuous use power: 40 KW / 50 KVA
Fuel: Diesel
Voltage: 230 V / 400 V
Frequency: 50 Hz
Motor: FPT NEF N67TM4
Engine speed: 1500 rpm
Starting: Electric
Consumption: 26 Lt/h at 75% load
Length: 3200 mm
Width: 1100 mm
Height: 2090 mm
Weight: 1950 Kg
Super-silenced
AVR

If you are looking for a product like the CGM 150F-C200 then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	44
Continuous power single phase (KW)	40
Maximum power single phase (KVA)	55
Continuous power single phase (KVA)	50
Maximum power three phase (KW)	132
Continuous power three phase (KW)	
Maximum power three phase (KVA)	
Continuous power three phase (KVA)	150
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	Morsettiera
Engine	FPT (IVECO) NEFN67TM4
Emissions Regulations	Stationary Use
Engine rpm (rpm)	1500
Speed governor	Mechanical
Starting system	Elettrico
Engine capacity (cm ³)	6700
Number cylinders	6
Cooling	Water
Alternator	Brushless
Poles	4
Protection degree	IP44
Bore x stroke (mm)	104 x 132
Fuel tank capacity (L)	250
Consumption (L/h)	26
Running time (h)	9.6
Acoustic pressure	69 dB(A) at 7 m
Length (mm)	3200
Width (mm)	1100
Height (mm)	2090
Dry weight (Kg)	350

AVR	Yes
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	FPT Iveco
