



GENSET MG 10/8 SS-KL SINGLE-PHASE / THREE-PHASE GENERATOR 10KVA

Reference: MG 10/8 SS-KL

GENSET MG 10/8 SS-KL SINGLE-PHASE / THREE-PHASE GENERATOR 10KVA

GENSET MG 10/8 SS-KL is a single-phase / three-phase generating set equipped with a Kubota D1105 (STAGE V) Diesel engine, capable of delivering a maximum power of 10KVA.

The GENSET MG 10/8 SS-KL generator set provides reliable power for home, business and recreational environments, safely powering appliances and other electronic devices.

The genset is as easy to install and operate as it is to start and stop with clear, intuitive controls. The GENSET MG 10/8 SS-KL is powered by a Kubota D1105 **STAGE V** Diesel engine. They are very reliable engines that guarantee efficient combustion and low fuel consumption, they are also equipped with a protection system that causes the engine to stop if the oil level is too low.

The GENSET MG 10/8 SS-KL has an all-steel construction and a large metal tank. The generator set guarantees an efficient and silent operation thanks to the Kubota D1105 which allows to deliver a maximum power of 10 KVA.

The generator set is supplied with:

- Battery 12 V
- 1 threephase socket CEE 400V - 16A
- 1 singlephase socket CEE 230V - 32A
- 1 singlephase socket CEE 230V - 16A
- Thermal protector
- Differential switch
- Emergency stop button
- Voltage selector
- Voltmeter
- Hour meter
- Central lifting hook
- Arrangement for operation in AMF-ATS or Remote control
- Glow plugs preheating warning light
- Automatic engine stop device with warning lights for:
 - battery failure
 - high water temperature
 - low oil pressure
 - low fuel level

TECHNICAL SPECIFICATIONS GENSET MG 10/8 SS-KL

Phase Type: SinglePhase/ThreePhase
Maximum SinglePhase Power: 6 KVA / 4.8 KW

Maximum ThreePhase Power: 10 KVA / 8 KW
 VAC Voltage: 230 / 400 V
 Frequency (Hz): 50
 Quadro Starter: Electric
 Motor: Kubota D1105
 Emission Standard: Stage V
 RPM: 1500
 Power supply: Diesel
 Fuel tank capacity: 30 l
 Consumption @ 75 % load: 2 l/h
 Autonomy @ 75 % load: 15 h
 Sound pressure: 90 dB(A)
 Length: 1360 mm
 Width: 675 mm
 Height: 860 mm
 Net weight: 350 kg

Are you looking for a generator set with different characteristics? [Here](#) you can find the full range of GENSET products or other brands specializing in the field

Images and technical data are not binding and may be subject to revision by the supplier.

Technical Sheet

| Phase | Single phase / Three phase |
|------------------------------------|--|
| Maximum power single phase (KW) | 4.8 |
| Maximum power single phase (KVA) | 6 |
| Maximum power three phase (KW) | 8 |
| Maximum power three phase (KVA) | 10 |
| Fuel | Diesel |
| Frequency (Hz) | 50 |
| Voltage (V) | 230 / 400 |
| Sockets configuration | 1 x 400V 16A CEE - 1 x 230V 16A CEE - 1 x 230V 32A CEE |
| Engine | Kubota D1105 |
| Emissions Regulations | Stage 5 |
| Engine rpm (rpm) | 1500 |
| Starting system | Electric |
| Engine capacity (cm ³) | 1123 |
| Number cylinders | 3 |
| Cooling | Water |
| Alternator | Synchronous |
| Protection degree | IP23 |
| Motor insulation class | H |
| Fuel tank capacity (L) | 30 |

| | |
|---------------------|-----------------|
| Consumption (L/h) | 2 |
| Running time (h) | 15 |
| Acoustic power | 90 dB(A) |
| Acoustic pressure | 65 dB(A) at 7 m |
| Length (mm) | 1360 |
| Width (mm) | 675 |
| Height (mm) | 860 |
| Dry weight (Kg) | 350 |
| Silenced | Yes |
| Super silenced | Yes |
| Product type | Generator |
| ATS Switch device | Optional ATS |
| Voltage regulator | No |
| Engine manufacturer | Kubota |