



CGM 250S-C300 WITH AUTOMATIC CONTROL PANEL

Reference: CGM 250S-C300 AUTOMATICO

CGM 250S-C300 Single/three-phase 250KVA generator with automatic control panel

The CGM 250S-C300 is a single/three phase 250KVA generator with a 1500 rpm Scania diesel engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproofed cabin made of structural steel plate, weatherproofing and an interior lining made of soundproofing material with high noise reduction, which makes the CGM 250S-C300 supersilenced. The CGM 250S-C300 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 250S-C300 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 38 litres per hour at 75% load. In addition, it has a control panel with automatic control unit and terminal box for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 250S-C300 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 250S-C300 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 220 KW / 275 KVA

Three-phase continuous power: 200 KW / 250 KVA

Maximum single-phase power: 73.33 KW / 91.67 KVA

Single-phase continuous use power: 66.67 KW / 83.33 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: SCANIA DC09 072A 02 11

Engine speed: 1500 rpm

Starting: Electric

Consumption: 38 Lt/h at 75% load

Length: 3700 mm

Width: 1400 mm

Height: 2250 mm

Weight: 2780 Kg

Super-silenced

AVR

If you are looking for a product like the CGM 250S-C300 then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	73.33
Continuous power single phase (KW)	66.67
Maximum power single phase (KVA)	91.67
Continuous power single phase (KVA)	83.33
Maximum power three phase (KW)	
Continuous power three phase (KW)	200
Maximum power three phase (KVA)	
Continuous power three phase (KVA)	250
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	Morsettiera
Engine	SCANIA DC09 072A 02 11
Emissions Regulations	Stationary Use
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Elettrico
Engine capacity (cm ³)	9300
Number cylinders	
Cooling	Water
Alternator	Brushless
Poles	4
Protection degree	IP44
Bore x stroke (mm)	130 x 140
Fuel tank capacity (L)	250
Consumption (L/h)	38
Running time (h)	6.6
Acoustic pressure	69 dB(A) at 7 m
Length (mm)	3700
Width (mm)	1400
Height (mm)	
Dry weight (Kg)	2780

AVR	Yes
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Scania
