



## NANNI QMS12M60 SILENT MARINE GENERATOR 12KW 60 HZ EPA TIER III

Reference: QMS 12M60

### NANNI QMS12M60 SILENT MARINE GENERATOR 12KW 60 HZ EPA TIER III

NANNI QMS12M60 is a single phase marine generator equipped with a Kubota EPA Tier III, 4-stroke diesel engine capable of delivering a maximum power of 12KW at 60Hz.

The NANNI QMS12M60 is equipped with a Kubota EPA tier III certified base engine used for years in marine and industrial applications worldwide.

The NANNI QMS12M60 generator is equipped with a fast-heating injector and glow plug and are located in the combustion chamber, ensuring that the engine will start even at low temperatures.

The cooling system allows the NANNI QMS12M60 to operate at an optimal temperature. In the case of closed-loop heat exchanger cooling, the coolant is cooled by seawater flowing through the heat exchanger.

The NANNI QMS12M60 is equipped with a closed-loop heat exchanger.

The E-TVCS injection system produces an ideal mixture of air and fuel by creating three swirls in the combustion chamber. The combustion efficiency of the NANNI QMS12M60 is improved, resulting in low fuel consumption.

NANNI QMS12M60 is complete with fresh and salt water exchanger and anti-noise cabin making it super quiet.

#### TECHNICAL FEATURES NANNI QMS12M60

Phase Type: Single Phase  
Maximum Power: 12 KVA / 12 KW  
Continuous Use Power: 10.7 KVA / 10.7 KW  
Fuel: Diesel  
Voltage: 120 - 240 V  
Frequency: 60 Hz  
Engine: Kubota, 4-stroke  
Emission Standard: EPA tier III  
Engine Revs. 1800  
Boosting: Electric  
Consumption: 4 Lt/h at full load  
Length: 1050 mm  
Width: 540 mm  
Height: 710 mm  
Weight: 291 Kg

Are you looking for a marine power generator with different technical features? [Here](#) you can find the full range of NANNI or other

brands specializing in the field.

The image and technical data are not binding and may be subject to revisions by the manufacturer.

## Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	12
Continuous power single phase (KW)	10.7
Maximum power single phase (KVA)	12
Continuous power single phase (KVA)	10.7
Fuel	Diesel
Frequency (Hz)	60
Voltage (V)	120 / 240
Engine	Kubota, 4 stroke
Emissions Regulations	EPA tier III
Engine rpm (rpm)	1800
Starting system	Electric
Number cylinders	4
Cylinders' position	In line
Cooling	Water
Inyección	Indirect (E-TVCS)
Alternator	Electronic regulator
Consumption (L/h)	4 at 100% of the load
Length (mm)	1050
Width (mm)	540
Height (mm)	710
Dry weight (Kg)	291
Silenced	Yes