



## HONDA FG 205 K1 DET MINI ROTARY TILLER 49 cc.

Reference: FG 205 K1 DE T

### HONDA FG 205 K1 DET MINI ROTARY TILLER 49 cc.

The HONDA FG205K1DET is a mini rotary tiller equipped with a gasoline-powered HONDA OHC GXV50 engine, capable of delivering a mechanical power of 1.3 KW.

The HONDA FG205K1 mini tiller is used to break up hard, compacted soil and optimally prepare it for planting. Ideal for small gardens, this effective rotary tiller is equipped with a robust 4-stroke engine that takes on the hard work.

HONDA FG205K1 mini is perfect not only for cultivating, but also for pulling weeds between rows of plants and taking the best care of the aesthetics of your flowerbeds. This tiller features a center carry handle, thanks to which it can be easily folded for easy transport and storage.

Thanks to the adjustable height handle the HONDA FG205K1 mini is perfect for operators of any height, plus, you can adjust the handlebar to the left or right so you can avoid compressing or stepping on the cultivated soil.

#### **TECHNICAL FEATURES HONDA FG205K1DET mini:**

Maximum working width: 450 mm  
Maximum working depth: 260 mm  
Forward speed: 1  
Forward rotation speed: 135 rpm.  
Engine: HONDA OHC GXV50, 4-stroke  
Displacement: 49 cc  
Engine net power: 1.3 KW  
Engine revs: 4800 rpm.  
Fuel tank capacity: 0.35 l  
Oil capacity: 0.3 l  
Start: Reel start  
Transmission clutch: Automatic - Centrifugal  
Transmission: Worm gear  
Sound pressure at operator's ear (dB(A)+): 79.5  
Guaranteed sound power level (dB(A)++): 93  
Vibration: 12.5 m/sec<sup>2</sup>  
Width: 1155 mm  
Depth: 510 mm  
Height: 1035 mm  
Dry weight: 21 kg

Looking for a rotary tiller with different technical characteristics? [Here](#) you can find the area dedicated to rotary tillers HONDA or other specialized brands.

## Technical Sheet

|                                    |                    |
|------------------------------------|--------------------|
| Fuel                               | Gasoline           |
| Engine                             | HONDA OHC GXV50    |
| Ignition                           | Recoil             |
| Starting system                    | Manual recoil      |
| Engine capacity (cm <sup>3</sup> ) | 49                 |
| Working width (mm)                 | 450                |
| Transmission                       | Ingranaggio a vite |
| Net power (kW)                     | 1.5                |
| Fuel tank capacity (L)             | 0.35               |
| Acoustic power                     | 93 dB(A)           |
| Acoustic pressure                  | 79.5 dB(A) @ 7m    |
| Length (mm)                        | 1155               |
| Height (mm)                        | 1035               |
| Dry weight (Kg)                    | 21                 |
| Self propelled                     | Yes                |
| Max tilling depth (mm)             | 260                |
| Engine manufacturer                | Honda              |