



CGM 400DS-C450 WITH AUTOMATIC CONTROL PANEL

Reference: CGM 400DS-C450 AUTOMATICO

CGM 400DS-C450 Single/three-phase 400KVA generator super-silenced with automatic control panel

The CGM 400DS-C450 is a single/three phase 400KVA generator with a 1500 rpm Doosan diesel engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproofed cabin made of structural steel plate, weatherproofing and an interior lining of soundproofing material with high noise reduction, which makes the CGM 400DS-C450 super-silenced.

The CGM 400DS-C450 generator consists of a Stamford, Mecc Alte or Marelli Motori, self-excited, brushless alternator with AVR voltage regulator. The CGM 400DS-C450 generator is equipped with an electric starter with a low fuel consumption battery, consuming only 65 litres per hour at 75% load. In addition, it has a control panel with automatic control unit and terminal box for automatic start-up.

This generator is perfect for use outdoors, such as on construction sites.

The CGM 400DS-C450 generator is part of the Industrial range and is characterised by its versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the CGM 400DS-C450 generator:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 376 KW / 470 KVA

Three-phase continuous power: 320 KW / 400 KVA

Maximum single-phase power: 125.33 KW / 156.67 KVA

Single-phase continuous use power: 106.67 KW / 133.33 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: DOOSAN P158 LE

Engine speed: 1500 rpm

Starting: Electric

Consumption: 65 Lt/h at 75% load

Length: 4300 mm

Width: 1750 mm

Height: 2350 mm

Weight: 4240 Kg

Super-silenced

AVR

If you are looking for a product like the CGM 400DS-C450 then you can browse the full range of CGM [generators](#) or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	125.33
Continuous power single phase (KW)	106.67
Maximum power single phase (KVA)	156.67
Continuous power single phase (KVA)	133.33
Maximum power three phase (KW)	376
Continuous power three phase (KW)	320
Maximum power three phase (KVA)	470
Continuous power three phase (KVA)	400
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	Terminal box
Engine	DOOSAN P158 LE
Emissions Regulations	Stationary Use
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Electric
Engine capacity (cm ³)	14618
Number cylinders	8
Cooling	Water
Alternator	Brushless
Poles	4
Protection degree	IP44
Bore x stroke (mm)	128 x 142
Fuel tank capacity (L)	400
Consumption (L/h)	65
Running time (h)	6.1
Acoustic pressure	69 dB(A) at 7 m
Length (mm)	4300
Width (mm)	1750
Height (mm)	2350

Dry weight (Kg)	4240
AVR	Yes
Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	AVR
Engine manufacturer	Doosan
