



BM2 DR 35 PROFESSIONAL DEHUMIDIFIER 35l/24h

Reference: 06DE121

BM2 DR35 PROFESSIONAL DEHUMIDIFIER 35l/24h

BM2 DR35 is a professional dehumidifier, autonomous, operating without the need for installation, simply by connecting a plug to the mains, capable of dehumidifying up to 35 l every 24 hours.

BM2 DR35 you have the ability to enter the desired humidity value via the handy digital display. The rest is regulated by the dehumidifier in a completely automatic way.

During operation you can see on the display of the BM2 DR35 the precise values of humidity and temperature in the room, as well as a diagnostic page where you can analyze the malfunctions and parameters of the refrigerant circuit.

The new and modern electronic control, together with the electronic humidistat as standard, optimizes the use of the dehumidifier making it work only when needed. The control panel of the BM2 DR35 is placed in a convenient location and easily accessible by the user, who can set the desired degree of humidity using the "soft touch" buttons.

The BM2 DR35 control panel is placed in a convenient location and easily accessible by the user, who can set the desired degree of humidity using the "soft touch" buttons.

The BM2 DR35 allows to dehumidify large working areas, such as warehouses, cellars, always maintaining the humidity level set by the user.

As standard, the electronic control manages two hour meters, one resettable and one cumulative: indispensable and practical for rental, several accessory pages and a diagnostic page where malfunctions and parameters of the refrigeration circuit can be analysed. BM2 DR35

TECHNICAL FEATURES BM2 DR35:

Phase type: Single-phase
Frequency: 50Hz
Dehumidification capacity: 35 l/24h
Airflow rate: 290 m³/h
Tank capacity: 7 l
Operating temperature: 3 - 40 °C
Operating humidity: 20 - 100 %

Compressor type: rotary
 Electrical power input: 0. 609W
 Refrigerant: R407C
 Protection class: IPX4
 Pressure acoustics: 56 dBA @ 1 m
 Dehumidifying capacity (@ 32°C - 90%): 35.18 l/24h
 Dehumidifying capacity (@ 30°C - 80%): 29.88 l/24h
 Dehumidifying capacity (@ 15°C - 70%): 14.04 l/24h
 Specific energy consumption (@ 32°C - 90%): 0.42 kWh/liter
 Specific energy consumption (@ 30°C - 80%): 0.46 kWh/liter
 Specific energy consumption (@ 15°C - 70%): 0.71 kWh/liter
 Width: 496 mm
 Depth: 470 mm
 Height: 724 mm
 Net weight: 40 Kg

BM2 DR35

Are you looking for a dehumidifier with different characteristics? [Here](#) you can find the full range BM2 or other brands specializing in the field

The images are purely indicative.

""

Technical Sheet

Phase	Single phase
Frequency (Hz)	50
Voltage (V)	230
Protection degree	IPX4
Air flow (m ³ /h)	290
Acoustic pressure	56 dBA @ 1 m
Length (mm)	496
Width (mm)	470
Height (mm)	724
Dry weight (Kg)	40
Container capacity (L)	7
Power consumption (W)	609
Coolant	R407C
Specific energy consumption (@ 32°C - 90%) kWh/liter	0.42
Specific energy consumption (@ 30°C - 80%) kWh/liter	0.46
Specific energy consumption (@ 15°C - 70%) kWh/liter	0.71
Dehumidification capacity (@ 32°C - 90%) l/24h	35.18
Dehumidification capacity (@ 30°C - 80%) l/24h	29.88

Dehumidification capacity (@ 15°C - 70%) l/24h

14.04