



GREEN POWER GP 6000XM/HM SINGLE PHASE GENERATOR STAGE V MANUAL START 4,5KVA

Reference: 00013X

GREEN POWER GP 6000XM/HM SINGLE PHASE GENERATOR STAGE V MANUAL START 4,5KVA

The Generator GREEN POWER GP 6000XM/HM single-phase is equipped with a HONDA GX270 **StageV** engine supplied by gasoline, and comes complete with capacitor voltage regulator (**AVR optional**).

GREEN POWER GP 6000XM/HM is equipped with manual recoil start with self-winding and has a low fuel consumption, in fact it consumes only 1,6 liter/hour at 75% load for a range of up to 3.3 hours of operation. Extremely practical sockets and controls facilitate the start-up and operation of the generator making these operations extremely simple and fast.

The generator is compact and convenient to maneuver and transport thanks to its compact size, its weight of 65 kg as well as the practical tubular handles.

The generator features an engine support system with a durable steel frame and rubber shock absorbers.

STAGEV EMISSION STANDARDS

The STAGEV standard defines guidelines and limits for engine gas emissions. The regulation is respected through the installation of special anti-particulate filters in the gensets, but an indispensable condition for the filter to work correctly is that the genset works at its design temperature.

TECHNICAL FEATURES GREEN POWER GP 6000XM/HM

Phase Type: Single-phase
Continuous Use Power: 4.1 KVA / 4.1 KW
Maximum Power: 4.5 KVA / 4.5 KW
Engine: HONDA GX270
Engine RPM: 3000 rpm
Emission Regulation: Stage V
Starting: Manual recoil
Fuel: Gasoline
Voltage: 230 V
Frequency: 50 Hz
Socket panel: 1 x Schuko 16A 230V / 1 x CEE 16A 230V
Tank capacity: 5.3 l
Autonomy at 75% of load: 3.3 h
Consumption at 75% of load: 1.6 Lt/h
Length: 700 mm
Width: 570 mm

Height: 630 mm
Dry weight: 65 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	4.5
Continuous power single phase (KW)	4.1
Maximum power single phase (KVA)	4.5
Continuous power single phase (KVA)	4.1
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x Schuko 16A 230V / 1 x CEE 16A 230V
Engine	HONDA GX270
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Pull starter with recoil
Engine capacity (cm ³)	270
Number cylinders	1
Cooling	Air
Alternator	LINZ SP10 MG
Poles	2
Fuel tank capacity (L)	5.3
Consumption (L/h)	1.6 al 75% del carico
Running time (h)	3.3 al 75% del carico
Length (mm)	570
Width (mm)	700
Height (mm)	630
Dry weight (Kg)	65
Silenced	No

Super silenced	No
ATS Switch device	No ATS
Voltage regulator	Capacitor / AVR (optional)
Engine manufacturer	Honda
