



GREEN POWER GP8000 XM/KM SINGLE-PHASE STAGE V GENERATOR MANUAL START 7,7KVA

Reference: 00005X

GREEN POWER GP8000 XM/KM SINGLE-PHASE STAGE V GENERATOR MANUAL START 7,7KVA

The generator GREEN POWER GP8000 XM/KM single-phase is equipped with a gasoline-supply KOHLER CH 440 StageV engine capable of delivering 7,7KVA at 3000 rpm.

The GREENPOWER GP8000 XM/KM generator alternator is the LINZ E1C10 MI model (or equivalent primary brand) and is synchronous, single-phase, with brushes and class H insulation. The GREENPOWER GP8000 XM/KM is equipped with manual recoil start with self winding.

One of the main features of the generator is the motor/alternator coupling in single bearing by means of cone, on electrowelded steel base with interposition of vibration dampers.

The GREENPOWER GP8000 XM/KM generator is compact and easy to maneuver and transport thanks to its compact size, its weight of 83 kg as well as the practical tubular handles. The generator with 6.1-liter tank has a fuel consumption of 2.1 liters/hour at 75% load.

STAGE V EMISSION STANDARDS

The STAGE V standard defines guidelines and limits for engine gas emissions. The regulation is respected through the installation of special anti-particulate filters in the gensets, but an indispensable condition for the filter to function correctly is that the genset works at its design temperature.

The electrical control panel of the generator is composed of:

- Output sockets: 1 x Schuko 16A 230V / 1 x CEE 32A 230V
- Thermal breaker
- Voltmeter

TECHNICAL FEATURES GREEN POWER GP8000 XM/KM

Phase type: Single-phase
Continuous use power: 7 KVA / 7 KW
Maximum power: 7.7 KVA / 7.7 KW
Motor: KOHLER CH 440
Engine speed: 3000 rpm
Emission regulation: StageV
Starting: Manual recoil
Fuel: Gasoline
Voltage: 230 V

Frequency: 50 Hz
Socket panel: 1 x Schuko 16A 230V / 1 x CEE 32A 230V
Tank capacity: 7 l
Autonomy at 75% load: 3.0 h
Consumption at 75% load: 2,3 Lt/h
Length: 780 mm
Width: 570 mm
Height: 680 mm
Dry weight: 85 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to GREEN POWER generators or other specialized brands.

Images and technical data are not binding.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	7.7
Continuous power single phase (KW)	7
Maximum power single phase (KVA)	7.7
Continuous power single phase (KVA)	7
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x Schuko 16A 230V / 1 x CEE 32A 230V
Engine	Kohler CH 440
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Manuale
Engine capacity (cm ³)	429
Number cylinders	1
Cooling	Air
Alternator	Linz
Poles	2
Fuel tank capacity (L)	7
Consumption (L/h)	2.3 al 75% del carico
Running time (h)	3 al 75% del carico
Length (mm)	780

Width (mm)	570
Height (mm)	680
Dry weight (Kg)	85
Silenced	No
Super silenced	No
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	Capacitor / AVR (optional)
Engine manufacturer	Kohler
