



GREEN POWER GP 6000XM/HE SINGLE-PHASE GENERATOR STAGE V ELECTRIC START 4,5KVA

Reference: 00016X

GREEN POWER GP 6000XM/HE SINGLE-PHASE GENERATOR STAGE V ELECTRIC START 4,5KVA

The generator GREEN POWER GP 6000XM/HE single-phase is equipped with a gasoline supplied HONDA GX270 **StageV** engine, and is complete with capacitor voltage regulator (**AVR optional**).

GREENPOWER GP 6000XM/HE generator is equipped with electric start and has a low fuel consumption, in fact it consumes only 1.6 liters/hour at 75% load for a range of up to 3.3 hours of operation. Extremely practical sockets and controls facilitate the start-up and operation of the generator, making these operations extremely simple and quick.

The generator is compact and convenient to maneuver and transport thanks to its compact size, its weight of 76 kg as well as the practical tubular handles. In addition it is equipped with a practical and convenient electric start system, so that it can be put into operation quickly and easily.

The generator is equipped with a high performance HONDA GX270 StageV engine which allows this machine to deliver a maximum single-phase power of 4.5KVA.

The front panel is composed of:

- Thermal breaker;
- 1 Schuko 16A 230V socket
- 1 CEE 16A 230V socket

TECHNICAL FEATURES GREEN POWER GP 6000XM/HE

Phase Type: Single Phase
Continuous Use Power: 4.1 KVA / 4.1 KW
Maximum Power: 4.5 KVA / 4.5 KW
Motor: HONDA GX270
Motor RPM: 3000 rpm
Emissions Standard: StageV
Boosting: Electric
Fuel: Gasoline
Voltage: 230 V
Frequency: 50 Hz
Socket panel: 1 x Schuko 16A 230V / 1 x CEE 16A 230V
Tank capacity: 5.3 l
Autonomy at 75% load: 3.3 h
Consumption at 75% load: 1.6 Lt/h

Length: 780 mm
Width: 570 mm
Height: 680 mm
Dry weight: 76 Kg

Are you looking for a generator with different technical characteristics? [Here](#) you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data not binding.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	4.5
Continuous power single phase (KW)	4.1
Maximum power single phase (KVA)	4.5
Continuous power single phase (KVA)	4.1
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x Schuko 16A 230V / 1 x CEE 16A 230V
Engine	HONDA GC160
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Elettrico
Engine capacity (cm ³)	160
Number cylinders	1
Cooling	Air
Alternator	LINZ SP10 MG
Poles	2
Fuel tank capacity (L)	5.3
Consumption (L/h)	1.6 al 75% del carico
Running time (h)	3.3 at 75% load
Length (mm)	570
Width (mm)	700
Height (mm)	630
Dry weight (Kg)	

Silenced	No
Super silenced	No
ATS Switch device	No ATS
Voltage regulator	Capacitor / AVR (optional)
Engine manufacturer	Honda
