



GREEN POWER GP 8000XT/KE SINGLE PHASE/THREE PHASE STAGE V GENERATOR ELECTRIC START 7,7KVA

Reference: 00004X

GREEN POWER GP 8000XT/KE SINGLE PHASE/THREE PHASE STAGEV GENERATOR 7,7KVA

The generator GREENPOWER GP 8000XT/KE single-phase/three-phase is equipped with a KOHLER CH 440 **StageV** gasoline-supplied engine, and is complete with Compound voltage regulator (**AVR optional**).

GREENPOWER GP 8000XT/KE has a low fuel consumption, in fact it consumes only 2.3 liters/hour at 75% load for a range of up to 3 hours of operation. Extremely practical sockets and controls make starting and operating the generator easy and quick.

The alternator of the GREENPOWER generator is the LINZ E1S10 MH model (or equivalent primary brand) and is synchronous, three-phase, with brushes and with class H insulation, in addition it is equipped with voltage regulator. The generator is ducted with a practical electric start system, so you can start the unit without any effort.

One of the main features of the GREENPOWER GP 8000XT/KE is the motor/alternator coupling in single bearing by means of a cone, on an electro-welded steel base with the interposition of anti-vibration mounts.

The StageV generator is compact and convenient to maneuver and transport thanks to its compact size, its weight of 95 kg as well as the practical tubular handles. In addition, it is equipped with a practical and convenient electric starting system, so that it can be started in a simple and fast way.

The GREENPOWER GP 8000XT/KE generator is equipped with KOHLER CH 440 StageV engine that allows this machine to deliver a maximum three-phase power of 7.7KVA.

STAGEV EMISSION STANDARDS

The STAGEV standard defines guidelines and limits for engine gas emissions. The regulation is respected through the installation of special anti-particulate filters in the gensets, but an indispensable condition for the filter to function correctly is that the genset works at its design temperature.

The electric control panel of the GREENPOWER GP 8000XT/KE is composed of:

- Output sockets: 1x 400V 16A CEE / 1x 230V 16A CEE
- Thermal circuit breaker
- Three-pole magneto-thermal switch
- Voltmeter

TECHNICAL FEATURES GREENPOWER GP 8000XT/KE

Phase Type: SinglePhase/ThreePhase
Continuous Use SinglePhase Power: 3.0 KVA / 2.4 KW

Maximum SinglePhase Power: 3.3 KVA / 2.7 KW
 Continuous Use ThreePhase Power: 7.0 KVA / 5.6 KW
 Maximum ThreePhase Power: 7.7 KVA / 6.2 KW
 Motor: KOHLER CH 440
 Motor Speed: 3000 rpm
 Emissions Standard: StageV
 Start: Electric
 Fuel: Gasoline
 Voltage: 230 / 400 V
 Frequency: 50 Hz
 Socket panel: 1 x CEE 16A 230V / 1 x CEE 16A 400V
 Tank capacity: 7 l
 Run time at 75% load: 3 h
 Consumption at 75% load: 2.3 Lt/h
 Length: 780 mm
 Width: 570 mm
 Height: 680 mm
 Dry weight: 95 Kg

Are you looking for a generator with different technical features? [Here](#) you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data not binding.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	2.7
Continuous power single phase (KW)	2.4
Maximum power single phase (KVA)	3.3
Continuous power single phase (KVA)	3
Maximum power three phase (KW)	6.2
Continuous power three phase (KW)	5.6
Maximum power three phase (KVA)	7.7
Continuous power three phase (KVA)	7
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 400V 16A CEE - 1 x 230V 16A CEE
Engine	Kohler CH 440
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000

Starting system	Elettrico
Engine capacity (cm ³)	
Number cylinders	1
Cooling	Air
Alternator	LINZ E1S10 MH
Poles	2
Fuel tank capacity (L)	7
Consumption (L/h)	2.3 al 75% del carico
Running time (h)	3 al 75% del carico
Length (mm)	780
Width (mm)	570
Height (mm)	680
Dry weight (Kg)	95
Silenced	No
Super silenced	No
Product type	Generator
ATS Switch device	No ATS
Voltage regulator	Compound / AVR (optional)
Engine manufacturer	Kohler