



GREEN POWER GP 6000XM/LM SINGLE-PHASE DIESEL GENERATOR STAGEV 5,6KVA

Reference: 00103X Condensatore

GREEN POWER GP 6000XM/LM SINGLE-PHASE DIESEL GENERATOR STAGEV 5,6KVA

The generator GREENPOWER GP 6000XM/LM single-phase is equipped with a KOHLER 15440 **StageV** engine supplied by Diesel, and is complete with capacitor voltage regulator (**AVR optional**).

GREENPOWER GP 6000XM/LM is equipped with manual recoil start with self winding and has a low fuel consumption, in fact it consumes only 1,6 liter/hour at 75% of load for a range of up to 3,1 hours of operation.

The GREENPOWER GP 6000XM/LM generator provides reliable power for home, work and recreation environments Safely appliances and other electronic devices Power solution for outdoor parties. Extremely convenient plugs and controls make starting and operating the generator easy and quick.

The GREENPOWER GP 6000XM/LM generator has a convenient double-curved handle for easy mobility and storage. GREENPOWER GP 6000XM/LM has a completely steel structure and a tank with a maximum capacity of 5 liters. The generator guarantees an efficient and silent operation thanks to the KOHLER 15440 StageV engine that allows to deliver a maximum power of 5,6KVA.

STAGEV EMISSION STANDARD

The acronym STAGEV defines the guidelines and limits of gas emissions from engines. The regulation is respected through the installation of special anti-particulate filters in the gensets, but an indispensable condition for the filter to work correctly is that the genset works at its design temperature.

TECHNICAL CHARACTERISTICS GREENPOWER GP 6000XM/LM

Phase Type: Single Phase
Continuous Use Power: 5 KVA / 5 KW
Maximum Power: 5.6 KVA / 5.6 KW
Motor: KOHLER 15440
Engine RPM: 3000 rpm
Emission Standard: StageV
Starting: Manual recoil
Fuel: Diesel
Voltage: 230 V
Frequency: 50 Hz
Socket panel: 1 x Schuko 16A 230V / 1 x 16A 230V CEE
Fuel tank capacity: 5 l
Autonomy at 75% load: 3.1 h
Consumption at 75% load: 1,6Lt/h
Length: 780 mm

Width: 570 mm
 Height: 680 mm
 Dry weight: 85 Kg

Are you looking for a generator with different technical characteristics? [Here](#) you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data not binding.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	5.6
Continuous power single phase (KW)	5
Maximum power single phase (KVA)	5.6
Continuous power single phase (KVA)	5
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 x Schuko 16A 230V / 1 x 16A 230V CEE
Engine	Kohler KD 15-440
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Pull starter with recoil
Engine capacity (cm ³)	436
Number cylinders	1
Cooling	Air
Alternator	LINZ SP10 MG
Poles	2
Fuel tank capacity (L)	5
Consumption (L/h)	1.6 al 75% del carico
Running time (h)	3.1 al 75% del carico
Length (mm)	780
Width (mm)	570
Height (mm)	680
Dry weight (Kg)	85
Silenced	No
Super silenced	No

ATS Switch device	No ATS
Voltage regulator	Capacitor / AVR (optional)
Engine manufacturer	Kohler
