



GREEN POWER GP 4000XM/LE SINGLE-PHASE GENERATOR ELECTRIC START DIESEL STAGEV 3,5KVA

Reference: 00107X

GREENPOWER GP 4000XM/LE SINGLE-PHASE GENERATOR ELECTRIC START DIESEL STAGEV 3,5KVA

The generator GREENPOWER GP 4000XM/LE single-phase, is equipped with a KOHLER KD350 **StageV** Diesel-supplied engine, complete with capacitor voltage regulator (**AVR optional**).

GREENPOWER GP 4000XM/LE is equipped with electric start and has a low fuel consumption, in fact it consumes only 1 liter/hour at 75% of load for a range of up to 4 hours of operation.

The generator provides reliable power for home, work and recreational environments, safely appliances and other electronic devices. Extremely convenient sockets and controls make starting and operating the generator easy and fast.

The GREENPOWER GP 4000XM/LE generator has a convenient double-curved handle for easy mobility and storage, has a completely steel structure and a tank with a maximum capacity of 4 liters. The generator guarantees an efficient and silent operation thanks to the KOHLER KD350 StageV engine with electric start, which can deliver a maximum power of 3.5KVA.

STAGEV EMISSION STANDARDS

The acronym STAGEV defines the guidelines and limits of gas emissions from engines. The regulation is respected through the installation of special anti-particulate filters in the gensets, but an indispensable condition for the filter to work correctly is that the genset works at its design temperature.

TECHNICAL FEATURES GREENPOWER GP 4000XM/LE

Phase Type: Single Phase
Continuous Use Power: 3.1 KVA / 3.1 KW
Maximum Power: 3.5 KVA / 3.5 KW
Motor: KOHLER KD350
Motor RPM: 3000 rpm
Emission Standard: StageV
Start: Electric
Fuel: Diesel
Voltage: 230 V
Frequency: 50 Hz
Socket panel: 2 x Schuko 16A 230V
Tank capacity: 4 l
Autonomy at 75% load: 4 h
Consumption at 75% load: 1 Lt/h
Length: 780 mm

Width: 570 mm
 Height: 680 mm
 Dry weight: 80 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to GREENPOWER generators or other specialized brands.

Images and technical data are not binding.

Technical Sheet

| | |
|-------------------------------------|----------------------|
| Phase | Single phase |
| Maximum power single phase (KW) | 3.5 |
| Continuous power single phase (KW) | 3.1 |
| Maximum power single phase (KVA) | 3.5 |
| Continuous power single phase (KVA) | 3.1 |
| Fuel | Diesel |
| Frequency (Hz) | 50 |
| Voltage (V) | 230 |
| Sockets configuration | 2 x 230V 16A SCHUKO |
| Engine | Kohler KD 350 |
| Emissions Regulations | Stage 5 |
| Engine rpm (rpm) | 3000 |
| Starting system | Elettrico |
| Engine capacity (cm ³) | 315 |
| Number cylinders | 1 |
| Cooling | Air |
| Alternator | LINZ SP10 SE |
| Poles | 2 |
| Fuel tank capacity (L) | 4 |
| Consumption (L/h) | 1 at 75% of the load |
| Running time (h) | 4 at 75% of the load |
| Length (mm) | 780 |
| Width (mm) | 570 |
| Height (mm) | 680 |
| Dry weight (Kg) | 80 |
| Silenced | No |
| Super silenced | No |

ATS Switch device

Optional ATS

Voltage regulator

Capacitor / AVR (optional)

Engine manufacturer

Kohler
