



MOSA GE 45 KSX GENERATOR 46 KVA AVR

Reference: CF1S70F1D

MOSA GE 45 KSX GENERATOR 46 KVA AVR

The MOSA GE45 KSX single / three-phase generator set is equipped with a diesel-powered Kohler KDI 2504 TM engine, and is capable of delivering a maximum power of 46 KVA.

The MOSA GE45 KSX generator is equipped with an electric starter with battery that allows it to be used quickly and easily even when cold. The group is equipped with a large 100-liter tank and has a fuel consumption of 7.1 liters / hour at 75% load for a range of more than 14 hours.

Thanks to the AVR voltage regulator included in the supply of the group, the MOSA GE45 KSX is able to supply "clean" current and voltage with an accuracy of less than one percent, this guarantees the user, to be able to safely connect any type of electrical and electronic device.

TECHNICAL CHARACTERISTICS OF MOSA GE45 KSX

Phase type: Singlephase / Threephase
Singlephase maximum power: 15.3 KVA / 12.3 KW
Singlephase continuous power: 14 KVA / 11.2 KW
Threephase maximum power: 46 KVA / 36.8 KW
Threephase continuous power: 42 KVA / 33.6 KW
Fuel: Diesel
Voltage: 230/400 V
Frequency: 50 Hz
Motor: KOHLER - KDI 2504TM- 40
Cooling: Water
Number of cylinders: 4
Engine revolutions: 1500 rpm
Starting: Electric
Voltage regulator system: AVR
Consumption : 7.1 Lt / h at 75% load
Tank capacity: 100 Lt
Autonomy: 14 h at 75% load
Acoustic pressure: 91 dB (A) (66 dB (A) @ 7m)
Length: 2050 mm
Width: 900 mm
Height: 1428 mm
Weight: 1033 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to MOSA generators or other specialized brands.

Non-binding images and technical data.

Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	12.3
Continuous power single phase (KW)	11.2
Maximum power single phase (KVA)	15.3
Continuous power single phase (KVA)	14
Maximum power three phase (KW)	36.8
Continuous power three phase (KW)	33.6
Maximum power three phase (KVA)	46
Continuous power three phase (KVA)	42
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	KOHLER KDI 2504TM-40
Emissions Regulations	Stage 3A
Engine rpm (rpm)	1500
Starting system	Electric
Engine capacity (cm ³)	3319
Number cylinders	4
Cooling	Water
Inyección	Direct
Alternator	Sincrono trifase, autoeccitato, autoregolato, senza spazzole
Fuel tank capacity (L)	100
Consumption (L/h)	7.1 at 75% of the load
Running time (h)	14 to 75% load
Acoustic pressure	66 dB(A) at 7 m
Length (mm)	2050
Width (mm)	900
Height (mm)	1428
Dry weight (Kg)	1033
Product type	Generator
ATS Switch device	Optional ATS

Voltage regulator	AVR
Engine manufacturer	Kohler
