



FINI BK 119-500F-7,5-AP HIGH PRESSURE COMPRESSOR 7,5 HP

Reference: BRTN801FNM875

FINI BK 119-500F-7,5-AP HIGH PRESSURE COMPRESSOR 7,5 HP

FINI BK 119-500F-7,5-AP is a high pressure compressor, equipped with a three-phase BK119 pump, capable of delivering a mechanical power of 7,5 Hp.

The Fini compressor is composed of powerful pumping groups that guarantee very high efficiency and reliability at the highest levels, capable of generating a pressure of 14 bar.

The FINI BK 119-500F-7,5-AP compressor combines a powerful and reliable group with a large air reserve, with a tank cable to contain up to 500 l of air, this makes this compressor suitable for all pneumatic accessories that require a high air consumption.

FINI BK 119-500F-7,5-AP is a two-cylinder lubricated belt-driven compressor, complete with electromechanical pressure switch with thermal relay protection.

FINI BK 119-500F-7,5-AP pumping group is equipped with large manifolds for a better cooling, complete with large size anti-vibration feet for a better stability during operation.

TECHNICAL SPECIFICATIONS FINI BK 119-500F-7,5-AP

Power supply phase: Three phase
Power supply voltage: 400 V
Power supply frequency: 50 Hz
Pump: BK119
Tank capacity: 500 l
RPM: 1045 RPM
Power: 5,5 KW - 7,5 HP
Air output: 705 Lt/min - 24.9 cfm
Pressure: 14 bar - 203 psi
BSP: 2"
Length: 2010 mm
Width: 650 mm
Height: 1330 mm
Dry weight: 266 Kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the area dedicated to FINI compressors or other specialized brands.

Images and technical data are not binding.

Technical Sheet

Phase	Three phase
Frequency (Hz)	50
Voltage (V)	400
Engine rpm (rpm)	1045
Power (KW)	5.5
Air output (L/min)	705
Mechanical power (hp)	7.5
Length (mm)	2010
Width (mm)	650
Height (mm)	1330
Dry weight (Kg)	266
Tank Capacity (l)	500