



BADA 10SE ELECTIRC LIFTER AISI 304 STAINLESS STEEL 1000Kg CAPACITY

Reference:

BADA 10SE ELECTIRC LIFTER AISI 304 STAINLESS STEEL 1000Kg CAPACITY

BADA 10SE is a lifter in stainless steel AISI 304 with electric lifting up to 2900 mm, designed to position goods at the ideal height and reduce the operator's effort during the operations of picking up and putting down the goods.

BADA 10SE thanks to its constructive characteristics, and to the construction entirely in **stainless steel AISI 304** can be used in the agri-food, chemical and pharmaceutical industry.

Resistant, easy to handle and with an ergonomic design, it fully meets the most stringent hygienic requirements as it can be sanitized by regular high-pressure washing. BADA 10SE is of side handles to direct the trolley and braking system on a directing wheel.

BADA 10SE is a manual lifter entirely made of AISI 304 stainless steel (including the lifting pump and hydraulic components), suitable for use in wet and corrosive environments where impeccable cleanliness and hygiene are required and corrosion problems caused by the use of acids and salt solutions must be solved. The bearings are waterproof and the rollers are made of nylon with a polyurethane cover making them extremely resistant and further minimizing maintenance costs.

The BADA 10SE lifter **ON EXPLICIT REQUEST OF THE CUSTOMER** can be supplied in AISI 316 stainless steel (**Optional WITH surcharge**).

TECHNICAL FEATURES BADA 10SE

Traction: Manual
Load center of gravity: 600 mm
Wheelbase: 1230 mm
Own weight including battery: 380 kg
Tire: polyurethane
Front wheels size: 175 x 40 mm
Rear wheels dimensions: 82 x 90 mm
Number of front / rear wheels: 2 / 2
Front track width: 683 mm
Rear track width: 380 mm
Lowered mast height: 2.078 / 1.978 mm
Fork lift stroke: 1.560 / 2.810 mm
Mast height extended: 2,078 / 3,340 mm
Height of drawbar in driving position min / max: 724 / 1.223 mm
Lowered fork height: 90 mm
Total length: 1,740 mm
Length including fork heel: 590 mm
Total width: 779 mm

Fork thickness: 55 mm
 Fork width: 180 mm
 Fork length: 1,150 mm
 Working aisle width: 1,860 mm
 Bending radius: 1.313 mm
 Lifting speed with / without load: 0.05 - 0.04 m/s
 Lowering speed with / without load 0.19 - 0.13 m/s
 Manual operating brake
 Construction material: Stainless steel AISI 304
 Lifting motor: 1.8 KW
 Voltage, nominal battery capacity 12 / 140 V/Ah

Are you looking for a pallet truck with different technical characteristics? [HERE](#) you can find the area dedicated to BADA or other Transpallet specialized brands.

Images and technical data are not binding.

Technical Sheet

Drive	Manual
Operator type	
Load capacity (Kg)	1000
Service weight (Kg)	320 / 380
Tyres: front wheels	POLY.I. / NYLON
Tyres: rear wheels	
Quantity rear wheels	2
Quantity front wheels	2
Rear balancing axle	No
Lift height (mm)	1650 / 2900
Height of tiller in drive position max (mm)	1223
Height of tiller in drive position min (mm)	724
Height lowered (mm)	90
Overall length (mm)	1740
Overall width (mm)	780
Width fork (mm)	180
Length fork (mm)	1150
Distance between fork arms (mm)	200
Turning radius (mm)	1313
Weigher	No
Type of lifting	Electric