



THREE-PHASE PTO GENERATOR 75KVA AVR

Reference: GP00812

THREE-PHASE PTO GENERATOR 75KVA

PTO Generator Three-phase, equipped with MECC ALTE ECP32-3L/4 alternator capable of delivering a power of 75KVA, complete with **AVR voltage regulator**.

The PTO generator is very reliable as it has been built and designed using top quality materials. The generator is easy to transport, install and position due to its compact size, this model is ideal to be mounted on a tractor unit.

The PTO generator for a correct operation, needs to be connected to a tractor capable of delivering a mechanical output of at least 150 HP and a PTO speed of at least 420 rpm. The minimum parameters indicated are necessary for the correct functioning of the PTO generator, if they are not respected it is possible to cause malfunctions of the equipment.

The generator is equipped with an electric panel complete with:

- Thermomagnetic circuit breaker
- Differential
- Socket 63 A 400 V
- Socket 16 A 230 V
- E31 digital module complete with: Voltmeter, Frequency meter and Hour meter

TECHNICAL FEATURES

Phase Type: Three Phase
Continuous output: 75 KVA
Continuous output: 60 KW
Voltage: 230 - 400 V
Frequency: 50 Hz
Motor RPM: 1500 rpm
Tractor Power Required: 150 hp
PTO RPM: 420 rpm
Alternator: MECC ALTE ECP32-3L/4 (OR EQUIVALENT)
No. of Poles: 4
Insulation Class: H
Protection Class: IP 23
Voltage Regulator: AVR
Length: 1140 mm
Width: 750 mm
Height: 1065 mm
Weight: 454 Kg

Are you looking for a PTO generator with different technical characteristics? [Here](#) you can find the full range of top quality brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

Technical Sheet

Phase	Three phase
Continuous power three phase (KW)	60
Continuous power three phase (KVA)	75
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine rpm (rpm)	1500
Alternator	MECC ALTE ECP32-3L/4
Poles	4
Protection degree	IP23
PTO speed (round/min)	420
Required tractor power	150 HP
Width (mm)	750
Height (mm)	1065
Dry weight (Kg)	454
Silenced	No
Super silenced	No
Voltage regulator	AVR