



GENERATOR SUPER SILENCED 11KVA SINGLE PHASE / THREE PHASE AVR MANUAL PANEL

Reference: GD11KVAM

GENERATOR SUPER SILENCED 11KVA SINGLE PHASE / THREE PHASE AVR MANUAL PANEL

The generator single-phase / three-phase is equipped with a Kohler KDW 1404 diesel-powered engine, capable of delivering a power of 11KVA with **AVR** voltage regulator.

This Generator is equipped with **electric start, manual** with 12 V battery, with panel and **LOVATO RGK 30** control unit that allows you to view the fuel reserve, the temperature water, oil pressure, battery voltage, belt integrity, high-low speed. In addition, it signals the enabled protections and the timing of the glow plugs

The Generator has a low fuel consumption, in fact it consumes only 2.5 liters / hour at 75% of the load, combined with a large tank of 70 liters of maximum capacity, it will give you an autonomy of about 28 hours.

The Generator guarantees efficient and silent operation thanks to the Kohler KDW 1404 engine, which allows to deliver a maximum power of 11KVA.

TECHNICAL FEATURES

Phase type: Single-phase / Three-phase
Continuous use power: 10 KVA / 8 KW
Maximum power: 11 KVA / 8.8 KW
Motor: Kohler KDW 1404
Emissions regulations : Not emitted
Engine revs: 1500 rpm
Starting: Electric / Manual
Fuel: Diesel
Voltage available at terminals (V): 230/400
Frequency: 50 Hz
Voltage regulator: AVR
Socket panel: 1 x CEE 16A 400V 5P / CEE 16A 230V 3P
Tank capacity: 70 l
Autonomy at 75% of the load: 28 h
Consumption at 75% of the load: 2,5 Lt / h
Acoustic pressure: 62 dB (A) @ 7 m
Length: 1750 mm
Width: 700 mm
Height: 1125 mm
Dry weight: 500 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the brand generators.

Non-binding images and technical data.

Technical Sheet

Phase	Single phase / Three phase
Maximum power three phase (KW)	8.8
Continuous power three phase (KW)	8
Maximum power three phase (KVA)	11
Continuous power three phase (KVA)	10
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	Kohler KDW 1404
Engine rpm (rpm)	1500
Speed governor	Mechanical
Starting system	
Engine capacity (cm ³)	1372
Number cylinders	4
Cylinders' position	In line
Protection degree	IP21
Fuel tank capacity (L)	70
Consumption (L/h)	2.5 al 75% del carico
Running time (h)	28 at 75% load
Length (mm)	1750
Width (mm)	700
Height (mm)	1125
Dry weight (Kg)	500
Silenced	Yes
Super silenced	Yes
ATS Switch device	No ATS
Voltage regulator	AVR