



## PTO Generator Single Phase 37.2 kVA/ Three Phase 93 kVA AVR

Reference: 183483-NB

### PTO Generator Single Phase 37.2 kVA/ Three Phase 93 kVA AVR

- For outdoor applications (field and home), in case of blackouts and in areas not served by the power grid
- Supplied with multiplier kit and protection, support with 3-point attachment (patented design), electrical panel with multifunction digital display for real-time data reading (voltmeter, frequency meter, ammeter, hour meter)
- Durability over time and maximum protection (thermal-magnetic and differential)
- Warranty 24 months
- Easy packaging and subsequent storage

#### Technical Data:

Phase: Single / Three Phase  
RPM: 1500  
Required tractor power (Hp): 285  
Single-phase power (kVA): 37.2  
Three-phase power (kVA): 93  
Pto Speed (rpm): 400  
Voltage (V): 230 / 400  
Frequency (Hz): 50  
Length (mm): 1204  
Width (mm): 640  
Height (mm): 923  
Weight (Kg): 382  
AVR

Non-binding images and technical data.

### Technical Sheet

Phase	Single phase / Three phase
Maximum power single phase (KW)	29
Maximum power single phase (KVA)	37.2
Maximum power three phase (KW)	74.4
Maximum power three phase (KVA)	93

Frequency (Hz)	50
Voltage (V)	230 / 400
Sockets configuration	1 x 400V 32A 3P+N+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V SCHUKO
Engine rpm (rpm)	1500
Protection degree	IP23
PTO speed (round/min)	400
Minimum tractor output (HP)	285
Transmission ratio	1 : 3.8
Length (mm)	1204
Width (mm)	640
Height (mm)	923
Dry weight (Kg)	382
Brushes	No
Voltage regulator	AVR