



PRAMAC GGW750G GENERATOR SILENCED 750KVA SINGLE/THREE PHASE NATURAL GAS AUTOMATIC CONTROL PANEL

Reference: SV621TXD002

PRAMAC GGW750G GENERATOR 750KVA SINGLE / THREE-PHASE NATURAL GAS

The PRAMAC GGW750G single-phase / three-phase generator set is equipped with a GENERAC G339 G-Drive motor **powered by natural gas**, capable of delivering a power of 750KVA complete with **AVR voltage regulator < / strong > and automatic control panel**.

The PRAMAC GGW750G is intended for emergency and non-continuous use. The PRAMAC GGW750G is equipped with **electric, manual or automatic start** with 12 V battery, equipped with the advanced Power Zone® control platform which includes all the functions to manage the gas group and perform a combustion optimum fuel, maximizing performance. It allows you to view all the parameters of the generator, the functions, the status of the generator, manage the entire group and view, if they occur, the errors or alarms of the system, in addition it is equipped with integrated remote control via Wi-Fi or Bluetooth.

PRAMAC GGW750G is equipped with a soundproof cabin, made of galvanized, folded and electro-welded sheet metal, with protection class IP23 with doors that can be opened for ordinary and extraordinary maintenance. The generating set guarantees efficient and silent operation thanks to the natural gas GENERAC G33.9 G-Drive engine, which allows to deliver a maximum power of 750KVA. In addition, this unit is equipped with electric or automatic starting via the ATS panel, which allows it to be switched on automatically in the event of a blackout.

ATS AUTOMATIC TRANSFER UNIT PREPARATION

The generator is set up for the use of an ATS automatic starting panel. Thanks to which you will no longer have to worry about blackouts because if it goes off the electricity grid this panel is able to automatically start the generator and will allow you to continue your business without losing your work data.

TECHNICAL FEATURES PRAMAC GGW750G

Type of phase: Single-phase / Three-phase
Continuous use power: 675 KVA / 540 KW
Maximum power: 750 KVA / 600 KW
Motor: GENERAC G33.9 G-Drive
Engine revolutions: 1500 rpm
Starting: Electric / Automatic
Fuel: Natural Gas
Voltage available at terminals: 230/400 V
Frequency: 50 Hz
Regulator voltage: AVR R450
Socket panel: Terminal block
Consumption at 75% of the load: 105 Kg / hr
Acoustic pressure: 73 dB (A) @ 7 m
Length: 6536 mm

Width: 2140 mm
 Height: 2810 mm
 Dry weight: 9950 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to PRAMAC generators or other specialized brands.

Non-binding images and technical data.

Technical Sheet

Phase	Single phase / Three phase
Maximum power three phase (KW)	600
Continuous power three phase (KW)	540
Maximum power three phase (KVA)	750
Continuous power three phase (KVA)	675
Fuel	Natural Gas
Frequency (Hz)	50
Voltage (V)	230 / 400
Engine	GENERAC G33.9 G-Drive
Engine rpm (rpm)	1500
Speed governor	Electronic
Starting system	Electric / Automatic
Engine capacity (cm ³)	33900
Number cylinders	12
Cylinders' position	V to 90°
Cooling	Water
Alternator	Leroy Somer LSA49.3 M6
Poles	4
Gas consumption (Kg/h)	105 to 75% load
Acoustic pressure	73 dB(A) at 7 m
Length (mm)	6536
Width (mm)	2140
Height (mm)	2810
Dry weight (Kg)	9950
Silenced	Yes
Super silenced	Yes
ATS Switch device	Optional ATS
Voltage regulator	AVR