



ECOFLOW DELTA PRO PORTABLE BATTERY 3,6 KW REMOTE CONTROL

Reference: 50034008

ECOFLOW DELTA PRO PORTABLE BATTERY 3,6 KW REMOTE CONTROL

The ECOFLOW DELTA PRO Portable Home Battery is a practical solution for having access, in any situation, to an ultra-quiet, zero-carbon energy source.

The ECOFLOW DELTA PRO Portable Home Battery has a capacity of 3.6 kWh that can be expanded up to 25 kWh. It can be integrated directly with home circuits via the Smart Home Panel. Ideal for home backup.

With 3600 W you could power heavy appliances such as dryers, air conditioners and more. Pair two units together to reach a whopping 7200 W..

ECOFLOW DELTA PRO you could expanded with additional batteries, generators and even the Smart Home Panel. You can control your ECOFLOW DELTA PRO portable battery via remote control or with your phone with the EcoFlow app. You can download the app for both [Android](#) and [ios](#), which is easy to install and features guidance on proper use.

The portable battery with the world's fastest charging DELTA Pro you could recharged by 6 methods, it can also do multiple charging by combining the methods to achieve 6500W fast charging.

The Delta Pro power station is designed to provide reliable and safe performance. It features an advanced management system to protect the battery from overcharging, short-circuiting and overheating. It also has a built-in LCD display that shows detailed information on battery charge and other settings.

ECOFLOW DELTA MAX TECHNICAL FEATURES:

INPUT

AC voltage: 220-240 VAC
AC power: 2875 W
Solar input: 1600 W, 11-150 Vdc 15A
Car charger input: 12 V / 24 Vdc 8 A

OUTPUT

n° 2 AC Schuko outputs: 3,6 KW continuous, 7,2 KW peak, 220 Vca, 50 Hz
n° 2 USB-A: 12 W per port, 5 Vcc, 2,4 A
n° 2 USB-A for fast charging: 18 W 5 Vcc, 2,4 A / 9V DC, 2 A / 12 Vcc, 1,5 A
n° 2 USB-C: 100 W 5/9/12/15/20 Vcc, 5 A
n° 1 auto output: 126 W 12,6 Vcc, 10 A
n° 2 outputs DC5521: 12,6 Vcc, 3 A
N° 1 Anderson output: 12.6 Vdc 30A

GENERAL INFORMATION

Solar charge connector: MC4
Single charge input power: 1600 W
Capacity: 3600 Wh
Cell type: LFP
Life cycle: 3500 cycles
Width: 635 mm
Length: 285 mm
Height: 416 mm
Weight: 44.9 kg

Looking for a Portable Batteries with different technical characteristics? [HERE](#) you can find the area dedicated to EcoFlow Portable Batteries and UPS or other specialized brands.

Non-binding images and technical data.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	7.2
Continuous power single phase (KW)	3.6
Maximum power single phase (KVA)	7.2
Maximum power three phase (KW)	3,6
Battery capacity (Wh)	3600
Length (mm)	635
Width (mm)	285
Height (mm)	416
Weight (Kg)	44.9
Video	ozVzv0jo_BM
Inputs	AC charging power: 2875 W / Solar input: 1600 W, 11-150 Vdc 15A / Car charger input: 12 V/24 Vdc 8 A
Outputs	2 x AC Schuko outputs / 2 x USB-A outputs: 5 Vdc, 2.4 A / 2 x USB-A for fast charging: 12 VDC, 1.5 A / 2 x USB-C output: 20 Vdc, 5 A / 1 x auto output: 12.6 VDC, 10 A / 2 x DC5521 outputs: 12.6 VDC, 3 A / 1 X Anderson output: 12.6 VDC, 30A
Life span	3500