



PRAMAC P4000 Generator Single-phase 3.5kVA STAGEV

Reference:

PRAMAC P4000 SINGLE-PHASE GENERATOR 3.5 KVA STAGE V

The PRAMAC P4000 single-phase generator with Yanmar L70V STAGE V diesel engine delivers 3.5 KVA of power and comes with capacitor voltage regulation (optional AVR).

The generator adapts perfectly to a wide range of uses thanks to the transport kit, which allows safe and easy relocation. With its enlarged 18 L tank, this generator offers an outstanding runtime of 15 h at 75% load.

These generators feature high-quality components, are lightweight and compact, easy to use, and boast a modern design with practical electric start.

The PRAMAC P4000 generator is equipped with electric start or automatic start via an ATS panel, enabling automatic start-up in the event of a blackout.

STAGE V EMISSIONS STANDARD

The generator set is equipped with a "mobile" STAGE V engine, as required by European Regulation 2016/1628. These new engines exponentially reduce particulate and nitrogen oxide emissions released into the environment, ensuring a 200% reduction in environmental impact compared to standard engines.

AUTOMATIC TRANSFER SWITCH (ATS) START PANEL (OPTIONAL)

The generator set is prearranged for use with an Automatic Transfer Switch (ATS) panel. Thanks to this, you no longer need to worry about blackouts: if the mains power fails, the panel can automatically start the generator so you can continue your activities without losing work data.

TECHNICAL FEATURES PRAMAC P4000 Single-Phase Generator 3.5kVA:

Phase type: Single-phase

Continuous power: 3.24 KVA / 2.92 KW

Maximum power: 3.57 KVA / 3.21 KW

Engine: Yanmar L70V

Engine speed: 3000 rpm

Emissions standard: STAGE V

Starting: Electric

Fuel: Diesel

Voltage: 230 V

Frequency: 50 Hz

Voltage regulation: Capacitor (optional AVR)

Socket panel: 1 x SCHUKO 230V 16A | 1 x CEE 230V 16A | 1 x CEE 230V 32A

Tank capacity: 18 L

Autonomy: 15.25 h at 75% load
 Consumption: 1.18 L/h at 75% load
 Sound pressure level: 68 dB(A) @ 7 m
 Length: 800 mm
 Width: 525 mm
 Height: 850 mm
 Dry weight: 132 kg

Looking for a generator set with different technical features? [HERE](#) you can find the section dedicated to PRAMAC generator sets and other specialized brands.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.2
Continuous power single phase (KW)	2.9
Maximum power single phase (KVA)	3.5
Continuous power single phase (KVA)	3.2
Fuel	Diesel
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	1 X SCHUKO 230V 16A 1 X CEE 230V 16A 1 X CEE 230V 32A
Engine	Yanmar L70V, 4 stroke
Engine rpm (rpm)	3000
Speed governor	Mechanical
Starting system	Elettrico
Engine capacity (cm ³)	320
Oil capacity (L)	1.01
Cooling	Air
Alternator	Brushless
Poles	2
Fuel tank capacity (L)	18
Consumption (L/h)	1.18 at 75% load
Running time (h)	15.25 at 75% load
Acoustic power	96 dB(A)
Acoustic pressure	68 dB(A) at 7 m
Length (mm)	800
Width (mm)	525
Height (mm)	850
Dry weight (Kg)	132

Silenced	Yes
Super silenced	Yes
Product type	Generator
ATS Switch device	Optional ATS
Voltage regulator	Capacitor / AVR (optional)
Engine manufacturer	Yanmar
