



## GENERATOR SINGLE PHASE SILENCED VEHICULAR 15,3KW STAGEV

Reference: GE VE MO SI 15KW

Generating Sets from 1 KVA to 2000 KVA with manual or automatic starting.

Thanks to such a wide range, GenSet is able to present specific solutions in the different fields of application of the genset both for continuous use and for emergency use in case of interruption of the main network.

All GenSet generating sets strictly comply with EC regulations on safety in use and control of polluting emissions.

The image is purely indicative

### Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	15.3
Continuous power single phase (KW)	13.9
Fuel	Diesel
Voltage (V)	230
Engine	Yanmar L70N
Engine rpm (rpm)	1500
Starting system	Electric
Engine capacity (cm <sup>3</sup> )	2190
Number cylinders	4
Cooling	Water
Alternator	Synchronous
Consumption (L/h)	4.4
Acoustic power	87 dB(A)
Acoustic pressure	62 dB(A) at 7 m
Length (mm)	1570
Width (mm)	650
Height (mm)	810

---

Dry weight (Kg)	550
Silenced	Yes
Super silenced	Yes
ATS Switch device	No ATS
Voltage regulator	AVR
Engine manufacturer	Yanmar

---