



## GENERATOR SINGLE PHASE STAGE V AVR 3,3 KW

Reference: GEB33KVA

### GENERATOR SINGLE PHASE STAGE V AVR 3,3 KW

Generator equipped with a gasoline-powered GENKINS 225 230M **StageV** engine, delivers a maximum power of 3.3KW, complete with AVR voltage regulator.

Equipped with **tear-off with self-wrapping**, equipped with AVR voltage regulator that allows connection with sensitive electronic devices (computers, smartphones, TVs) without the risk of damaging them due to surges in the current power supply.

The generator provides reliable power for home, business and leisure environments, safely powers home appliances and other electronic devices. Extremely practical sockets and controls make starting and operating the generator easier, making these operations extremely simple and fast.

The generator has a practical double curved handle and integrated towing trolley, to facilitate mobility and storage. structure completely in steel and a tank with a maximum capacity of 15 liters that allows the generator to run for about 6.5 hours at full load.

### STAGEV EMISSIONS REGULATION

Equipped with "mobile" STAGEV motorization, as required by the European Regulation 2016/1628. These new engines make it possible to exponentially reduce the emissions of particulate matter and nitrogen oxides delivered by the generator into the environment, and ensure a reduction in the environmental impact of 200% compared to standard engines.

#### TECHNICAL FEATURES

Type of phase: Single-phase  
Continuous use power: 3 KVA / 3 KW  
Maximum power 3.3 KVA / 3.3 KW  
Motor: GENKINS 225 230M  
Motor revolutions: 3000 rpm  
Emissions standard: StageV  
Starter: Pull-off with wrap-around car  
Fuel: Petrol  
Voltage: 230 V  
Frequency: 50 Hz  
Socket panel: 2 x schuko 16A 230 V  
Tank capacity: 15 l  
Fuel consumption (100% of PRP): 2.3 l / h  
Autonomy: 6.5 h  
Acoustic pressure: 71 dB (A) @ 7 m  
Voltage regulator: AVR  
Length: 615 mm

Width: 470 mm  
Height: 480 mm  
Net weight: 45 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to specialized brand generators.

Non-binding images and technical data.

## Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.3
Continuous power single phase (KW)	3
Maximum power single phase (KVA)	3.3
Continuous power single phase (KVA)	3
Fuel	Gasoline
Frequency (Hz)	50
Voltage (V)	230
Sockets configuration	2 x schuko 16A 230 V
Engine	GENKINS 225 230M
Emissions Regulations	Stage 5
Engine rpm (rpm)	3000
Starting system	Pull starter with recoil
Fuel tank capacity (L)	15
Consumption (L/h)	2.3 at 100% of the load
Running time (h)	6.5
Acoustic pressure	71 dB(A) at 7 m
Length (mm)	615
Width (mm)	470
Height (mm)	480
Dry weight (Kg)	45
Silenced	Yes
Super silenced	No
ATS Switch device	No ATS
Voltage regulator	AVR