



EcoFlow Get Set Kit

Reference: 5001801009

EcoFlow Get Set Kit

EcoFlow Power kits are the world's first development of integrated energy independence systems. These systems are easy to install and use (plug and play), smart features and compact size. The compactness allows the use of the Power Kits not only in fixed residential buildings, but also in vehicles.

Unlike many other kits, Power Kits are compact. To save space, EcoFlow has pared down the traditional power package with thin wires and compact batteries. That's why you can easily hide the Power Hub, batteries and other system components in a small closet or even under the seat.

Energy Independence Kits offer a safe 48V power solution. A 48V system produces the same amount of power, but compared to 12V systems, only a quarter of the electrical current passes through the cables, resulting in much less heat loss and power.

ECOFLOW GEN SET KIT TECHNICAL SPECIFICATIONS

Pure sine wave AC output, 3600W (7200W flux), 120V, 50/60Hz.
DC output 13.6V / 70A, 1000W max; 26.4V / 60A, 1600W max;
AC input X-Stream fast charging 3000W max, 15A max.
AC input voltage 220-240V, 50/60Hz
< br / > Solar charging inputs 15-150V 30A, 1600W max.
Alternator charging inputs 13-60V 60A, 1600W max.
Operating temperature -25°C - 60°C
Storage temperature -25°C - 60°C
Charge temperature -25°C - 60°C
Discharge temperature -25°C - 60°C
< br / > Width: 480 mm
Length: 140 mm
Height: 300 mm
Weight 14 kg

Discover the entire range of Ecoflow products [by clicking HERE!](#)

The images and technical characteristics are not binding and may be subject to revisions by the manufacturer.