



Vitrifrigo Seawater Pump 3360 Lt/h

Reference: WPPMD641.230/50

VITRIFRIGO SEAWATER PUMP 3360 LT/H

The VITRIFRIGO Seawater Pump \magnetic drive\" represents an excellent solution for refrigeration and water distribution needs aboard yachts and boats. This VITRIFRIGO pump is designed with advanced technology and innovative features to ensure optimal performance and lasting reliability, making it an ideal choice for sailing enthusiasts seeking maximum comfort on board.

With a single-phase and a voltage of 230 V, this VITRIFRIGO pump offers a frequency of 50 Hz, absorbing only 0.60A of current, making it energy efficient and ideal for long-term use without concerns of overheating or overload.

Featuring 26 mm inlet and outlet, this VITRIFRIGO pump ensures a smooth and uniform distribution of seawater, with an impressive flow rate of 3360 liters per hour. This high flow rate guarantees quick and effective cooling of onboard systems, keeping environments fresh even on the hottest days.

The compact and robust construction of the VITRIFRIGO Seawater Pump makes it suitable for limited spaces on board, with dimensions of only 230 mm in length, 115 mm in width, and 155 mm in height. The VITRIFRIGO Sea Water Pump can handle heavy loads and ensure reliable water distribution at all times.

With a weight of 4.8 kg, it ensures optimal stability during installation and use, while the ergonomic design simplifies maintenance and cleaning operations to keep the VITRIFRIGO pump in optimal condition over time.

In conclusion, the VITRIFRIGO Seawater Pump \magnetic drive\" is an excellent choice for anyone seeking high performance, energy efficiency, and lasting reliability aboard yachts and boats. Thanks to their advanced technology and innovative features, this VITRIFRIGO pump ensures smooth operation and uniform seawater distribution, contributing to enhancing the sailing experience and crew comfort.

Technical characteristics VITRIFRIGO Seawater Pump:

Phase type: Single-phase
Voltage: 230 V

Frequency: 50 Hz
Current absorbed: 0.60 A
Water inlet: 26 mm
Water outlet: 26 mm
Flow rate: 3360 l/h
Length: 230 mm
Width: 115 mm
Height: 155 mm
Weight: 4.8 Kg

Are you looking for a marine air conditioner? [HERE](#) you can find the area dedicated to Vitrifrigo marine air conditioners or other specialized brands.

Non-binding images and technical data.

""

Technical Sheet

Phase	Single phase
Frequency (Hz)	50
Voltage (V)	230
Length (mm)	230
Width (mm)	115
Height (mm)	155
Dry weight (Kg)	4.8
Capacity (Lt/h)	3360
Absorbed current (A)	0.60