



GENERAC LT VTEVOQ LIGHT TOWER 4x320W G4 LED WITH GENERATOR 5KW STAGEV

Reference: LS06K20-0000EU

GENERAC LT VTEVOQ LIGHT TOWER 4x320W G4 LED WITH GENERATOR 5KW STAGEV

GENERAC LT VTEVOQ is a light tower equipped with four 320W Led floodlights that can be lifted up to a height of 7,5 m, capable of illuminating an area of 4500 m².

The GENERAC LT VTEVOQ is equipped with a Kubota Z482 StageV Diesel engine, which in combination with the capacious 120 l tank manages to guarantee a working autonomy of 171 h. The GENERAC LT VTEVOQ has an extremely quiet operation, in fact it has a sound emission of only 63 dB(A) at 7m.

The Generac LT VTEVOQ, thanks to 4 LED floodlights can illuminate an area of 4500 square meters with a maximum luminous intensity of 188160 lm total. The light tower is equipped with a galvanized mast with a winch manual system that allows the floodlights to be raised to a maximum height of 7.5m. The winch is equipped with an anti-fall safety system that blocks its access and accidental release once positioned.

Ideal for lighting construction sites, parking lots, emergency sites, outdoor events, and other applications where intense, long-lasting illumination is needed in low light conditions.

TECHNICAL FEATURES GENERAC LT VTEVOQ

Lamp power: 4 x 320 W
Lamp type: LED
Total lumens: 188160 Lm
Illuminated area: 4500 m²
Lifting system: Manual
Pole rotation: 340°
Engine: Kubota Z482
Emission standard: StageV
Engine Cooling: Liquid
Cylinders (N): 2
Engine speed (50/60 Hz): 1500 / 1800 rpm
Alternator (kVA/V/Hz): 3.5/220/50 - 4.2/240/60
Electrical outlet (kVA/V/Hz): 2/220/50 - 2/240/60
Average sound pressure: 63 dB(A) @ 7m
Wind resistance: 80 km/h
Tank capacity: 120 l
Autonomy: 171 h
Minimum dimensions (W x D x H): 2480 x 1190 x 1950 mm
Maximum dimensions (W x D x H): 2480 x 2400 x 7500 mm
Dry weight: 620 kg

Are you looking for a product with different technical characteristics? [HERE](#) you can find the towers or other specialized brands.

Non-binding images and technical data.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	3.5
Maximum power single phase (KVA)	3.5
Fuel	Diesel
Voltage (V)	230
Engine	Kubota Z482
Emissions Regulations	Stage 5
Engine rpm (rpm)	1500 / 1800
Number cylinders	2
Cooling	Coolant Liquid
Type of lamps	LED
Lamps	4 x 320 W
Illuminated area (m ²)	4500
Total lumens (Lm)	188160
Lifting System	Manual lifting system
Maximum height (m)	7.5
Mast rotation	340°
Open size (mm)	2480 x 2400 x 7500
Closed size (mm)	2480 x 1190 x 1950
With generator / Without generator	With generator
Transportability	Stationary
Stability to wind (Km/h)	80 Km/h
Fuel tank capacity (L)	120
Running time (h)	171
Acoustic pressure	63 dB(A) at 7 m
Dry weight (Kg)	620
Engine manufacturer	Kubota