



## HONDA GX200 SXE5 Gasoline Engine 4.4 HP

Reference: GX200 SXE5

### HONDA GX200 SXE5 Gasoline Engine 4.4 HP

HONDA GX200 SXE5 engines are recommended for a wide range of professional machines in the fields of construction, agricultural machinery, power generators, power welders, motor pumps, and other industrial applications.

#### TECHNICAL SPECIFICATIONS HONDA GX200 SXE5

Engine type: OHV horizontal shaft, eight cycle, 4-stroke  
Number of cylinders: 1  
Cylinder Arrangement: 25° inclined  
Bore x stroke: 68 x 54 mm  
Displacement: 196 cm<sup>3</sup>  
Cooling: Forced air  
Compression ratio: 8.5 : 1  
Net power: 4.1 kW (5.5 HP) / 3 600 rpm  
Continuous rated power 3000 rpm: 3.3 kW (4.4 HP)  
Continuous rated power 3600 rpm: 3.7 kW (5.0 HP) / 3 600 rpm  
Maximum torque: 12.4 Nm / 1.26 kgfm / 2 500 rpm  
Ignition: Contactless transistor  
Starting: Recoil with recoil starter  
Fuel tank capacity: 3.1 liters  
Fuel consumption at rated power: 1.7 Liters/hour - 3 600 rpm  
Oil pan capacity: 0.6 Liters  
Length: 313 mm  
Width: 376 mm  
Height: 346 mm  
Net Weight: 16 kg

Looking for an engine with different technical characteristics? HERE you can find the area dedicated to HONDA engines or other specialized brands.

Images and technical data are not binding and may be subject to revision.

#### Technical Sheet

Fuel	Gasoline
Engine	OHV horizontal shaft, eight cycle, 4-stroke

Ignition	A transistor contactless
Starting system	Manual
Engine capacity (cm <sup>3</sup> )	196
Number cylinders	1
Cylinders' position	Inclined to 25°
Oil capacity (L)	0.6
Cooling	Forced air
Bore x stroke (mm)	68 x 54
Compression ratio	8.5 : 1
Net power (kW)	4.1
Nominal power continuous	3.3 KW (4.4 HP) / 3000 rpm - 3.7 KW (5.0 HP) / 3600 rpm
Maximum torque	12.4 Nm / 1.26 kgfm / 2500 rpm
Fuel tank capacity (L)	3.1
Consumption (L/h)	1.7
Running time (h)	1.82
Length (mm)	321
Width (mm)	376
Height (mm)	346
Dry weight (Kg)	16.1
Engine manufacturer	Honda