Man.El.Service Srl
Torino: +39 011 25 35 33 | Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

WHISPER M-SQ PRO 15 MARINE GENERATOR 15KVA SINGLE-PHASE AVR

Reference: 41207005

WHISPER M-SQ PRO15 SINGLE-PHASE MARINE GENERATOR 15KVA AVR

WHISPER M-SQ PRO15 Single-phase marine generator with Kubota V1505 BG engine powered by diesel, delivers a power of 15KVA, **complete with AVR voltage regulator**.

The marine generator is standard equipped with a robust acoustic capsule with anti-corrosion metal plating and insulating material for optimal sound reduction. The hearing protector features easy access to all sides of the marine generator and offers access to all maintenance-related components from one side only.

Each WHISPER M-SQ PRO15 is designed for non-stop operation at 1500 rpm in difficult conditions. The engine is water-cooled and kept at a constant temperature via a heat exchanger.

Thanks to the AVR technology electrical stabilizer that works at very low distortion, WHISPER M-SQ PRO15 delivers constant current loads without voltage peaks that could damage electrical and electronic devices. A further advantage of the inverter is that it works with variable motor revolutions, based on the need for the current to be supplied, optimizing fuel consumption, gas emissions and wear of the mechanical parts in the best possible way. Automatically operate air conditioning/heating systems, heavy tools, compressors, cookers, lights, refrigeration and cooling systems, computers and more. All at the same time, depending on the load.

The Whisper M-SQ Pro15 was designed to work efficiently and reliably in marine environments, thanks to its rust-free, corrosion-resistant and saltwater construction. Furthermore, the marine generator is very silent and offers a low emission of polluting substances, guaranteeing to provide an ecologically sustainable solution.

AVR VOLTAGE REGULATOR

WHISPER M-SQ PRO15 is equipped with AVR which, mounted on an alternator, allows a marine generator to stabilize the output voltage and does not damage the connected sensitive electronic devices. In the modern market, AVR have made a huge step forward in terms of technology and performance; for this reason the best brands of generator sets and alternators in the world are moving along this line of thought.

An important feature of the SQ Pro range is the 7 inch color touch screen control which will be linked with WhisperCare. This allows complete control of the M-SQ Pro15 system. A perfect solution for instantaneous and/or historical information with an attractive display.

DeepSea Control Features (Optional)

- Group parallel functionality included (ask for more details)
- Provides secure and easy offsite monitoring (optional)
- Allows you to quickly resolve fault conditions and provide instant system information to aid in preventive maintenance

Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

- Graphic displays showing, graphs, meters, power display, graphs and engine status information
- The information is displayed clearly and in a universal format for all users
- Language of your choice

Technical characteristics WHISPER M-SQ PRO15:

Phase Type: Single Phase
Maximum Power: 15.6 KVA / 12.5 KW
Continuous Power: 15 KVA / 12 KW
Fuel: Diesel
Voltage: 230 V
Frequency: 50 Hz (60 Hz)
Engine: Kubota V1505 BG
Emissions standard: Not Emissions
Number of cylinders: 4
Engine speed: 1500 rpm
Power acoustics: 55 dBA
Voltage regulator: AVR
Length: 1145 mm
Depth: 625 mm
Height: 690 mm
Net weight: 410 Kg

Are you looking for a product with different technical characteristics? HERE you can find the area dedicated to WHISPER marine generators or other specialized brands.

Non-binding images and technical data.

Technical Sheet

Phase	Single phase
Maximum power single phase (KW)	12.5
Continuous power single phase (KW)	12
Maximum power single phase (KVA)	15.6
Continuous power single phase (KVA)	15
Fuel	Diesel
Frequency (Hz)	50 / 60
Voltage (V)	230
Engine	Kubota V1505 BG
Emissions Regulations	Not Emitted
Engine rpm (rpm)	1500
Number cylinders	4
Cooling	External radiator cooling
Acoustic pressure	55 dB(A)
Length (mm)	1145

Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

Width (mm)	625
Height (mm)	690
Dry weight (Kg)	410
Silenced	Yes
Super silenced	Yes
Product type	Generator
Voltage regulator	AVR
Engine manufacturer	Kubota