

OSMOSEA NEW12S 25 NAUTICAL WATERMAKER 25 LT/H

Reference: A-0000000061



OSMOSEA NEW12S 25 NAUTICAL WATERMAKER 25 LT/H

The OSMOSEA NEW12S 25 desalinator is designed to be used as a watermaker. a monobloc reverse osmosis system equipped with 1 carbon vessel 2521 , capable of supplying up to 25 l/h of fresh water.

Designed to remove salt and other impurities from the skin. from sea or brackish water, ideal for use on board boats and yachts, but may also be used in other situations such as campsites, mountain shelters and isolated homes.

The watermaker is ready. capable of producing up to 25 liters of purified water per hour, depending on salinity conditions; and ambient temperature. The system is also equipped with sensors and automatic controls to ensure safe and efficient operation.

OSMOSEA NEW12S 25 able to remove 99.4%, making it safe for consumption. Thanks to the removal of the salt, the water has a neutral taste and can be polluted. be used for drinking, cooking and washing.

The OSMOSEA NEW12S 25 water maker is supplied complete with:

- ? Remote Panel.
- ? Watermaker digital control unit.
- ? Sea water supply pump.
- ? N. 1 Pre-filter with pre-installed cartridge.
- ? N. 1 Post filter with pre-installed Carbon cartridge.
- ? N. 1 Flushing Filter with pre-installed Carbon cartridge.
- ? N. 1 Anti-Algae Filter.
- ? N. 1 Tee with Non-return Valve.

TECHNICAL FEATURES OSMOSEA NEW12S 25

Production: 25 l/h
Daily production: 600 l/day
Number of Vessels: 1
Vessel type: 2521 in Carbon
Membranes: high efficiency
Salt expelled: 99.4%
Pressure adjustment: Automatic
Salinity monitoring: Automatic
Salinity: Automatic maximum use: 50000 ppm
Power supply voltage: 12 / 24 V
Installed power: 100 KW
Frame: INOX
Length: 738 mm

Width: 175 mm
Height: 290 mm
Net weight: 24 kg

Are you looking for a watermaker with different features? [HERE](#) you can find the area dedicated to OSMOSEA watermakers or other specialized brands.

Non-binding images and technical data.

Technical Sheet

Power (W)	100
Length (mm)	738
Width (mm)	175
Height (mm)	290
Feed Type	12 / 24 VDC
Production for hour at 25°C (Lt/h)	25
Daily production at 25°C (Lt/day)	600
Membranes	n.12.5" x 21"
Remote panel	Basic
Product type	Watermaker
Weight (Kg)	24