

CUMMINS GTEC 500A AUTOMATIC TRANSFER SWITCH



Reference: GT40500UN72

CUMMINS GTEC 500A AUTOMATIC TRANSFER SWITCH

CUMMINS GTEC 500A Transfer Switch, a reliable ATS designed to ensure continuous power during power outages. With its state-of-the-art technology and rugged construction, this transfer switch is the ideal accessory for Cummins generators. Offering a smooth transition between main and emergency power, the CUMMINS GTEC 500A ensures you have a steady flow of power, protecting your electrical devices from potential damage. Entrust your energy security to GTEC Transfer Switch.

The CUMMINS GTEC 500A is the ultimate solution for ensuring reliable power in every situation. This state-of-the-art transfer switch is designed to enable a smooth transition between main and emergency power. Learn more about the features and benefits that make the CUMMINS GTEC 500A an indispensable component of your power grid.

The CUMMINS GTEC 500A features state-of-the-art technology that ensures its reliability and superior performance. With its high-quality components and advanced design, this transfer switch gives you the peace of mind that your power supply will be constant and stable, even during emergency situations.

With the CUMMINS GTEC 500A, you won't have to worry about power outages. This device automatically activates in the event of a power outage, seamlessly switching to the emergency power supplied by Cummins generators. This means your electrical devices will continue to operate without any interruption, avoiding damage and inconvenience caused by momentary power surges.

CUMMINS GTEC 500A TECHNICAL FEATURES

Number of poles: 4
Ampere range: 500 A
Application Voltage: Multi-voltage 110/119 to 277/480 V
Control Type: 12 Vdc
Frequency: 50/60 Hz
Protection class: IP 32
Length: 950 mm
Width: 650 mm
Height: 231 mm
Weight: 63 Kg

Looking for an ATS switchboard with different technical characteristics? [HERE](#) you can find the area dedicated to automatic switchboards from CUMMINS or other specialized brands.

Images and technical data are not binding and may be subject to revision.

Frequency (Hz)	50 / 60
Poles	4
Protection degree	IP32
Current range (A)	50 - 500
Length (mm)	950
Width (mm)	650
Height (mm)	231
Product type	Switching Frame
Colour	Grey
Weight (Kg)	63