Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

OSMOSEA CLASSIC 340L NAUTICAL/LAND FACILITIES WATERMAKER 720 LT/H

Reference: A-0000002817

OSMOSEA CLASSIC 340L NAUTICAL/LAND FACILITIES WATERMAKER 720 LT/H

The OSMOSEA CLASSIC 340L watermaker is a one-piece reverse osmosis plant equipped with 3 vessels, capable of supplying up to 720 lt/h of fresh water.

The Osmosea Classic 340L watermaker is easy to operate and requires little maintenance. The system is equipped with an intuitive control panel, making it easy to monitor and adjust the flow and quality of the water produced. The system also features a self-wash function, which keeps the membranes and filters clean and in good condition over time.

With a production capacity of 720 liters per hour, this watermaker can provide a considerable amount of fresh water to meet the needs of large boats, yachts, or land locations where drinking water is limited.

The desalination system is compact and easily installed in both marine and land environments. It features a sturdy stainless steel frame that ensures the strength and durability of the product. The OSMOSEA Classic 340L watermaker is designed to operate quietly and with low power consumption, offering optimal efficiency in terms of both fresh water production and energy resources.

The watermaker is sold complete with:

- Stainless Steel Feed Pump
- Pre-filters
- Post-filter
- System Control Unit with Micro Computer
- Installation Kit (piping, fittings, hose clamps)
- Maintenance Kit (No.1 spare filter set, Filter Wrench, Cleaning and winterization products, High Pressure Pump Oil)
- Membrane Flushing System

TECHNICAL CHARACTERISTICS OSMOSEA CLASSIC 340L

Production: 720 lt/h
Daily Production: 17280 lt/day
Vessel Number: 3
Vessel Type: 4040 Carbon
Membranes: Tri-polyamide high efficiency
Expelled Salt: 99.4%
Pressure Adjustment: Manual
Salinity monitoring: Automatic
Maximum use salinity: 50000 ppm
Power supply voltage: 400 V
Frequency: 50 Hz

Man.El.Service Srl
Torino: +39 011 25 35 33 I Milano: +39 02 83 62 30 79
info@manelservice.com
Via Carlo Pittara 46 - 10151 Torino (TO) - Italy
PIVA 09031950018 - Num. REA: 1020262
SDI 5RUO82D Cap. Soc. € 20.000 I.V

Installed power: 6.7 KW
Frame: stainless steel
Length: 1265 mm
Width: 573 mm
Height: 618 mm
Weight: 83 kg

Looking for a watermaker with different features? HERE you can find the area dedicated to watermakers OSMOSEA or other specialized brands.

Images and technical data not binding.

Technical Sheet

Power (W)	6700
Length (mm)	1265
Width (mm)	573
Height (mm)	618
Dry weight (Kg)	83
Feed Type	400 V
Production for hour at 25°C (Lt/h)	720
Remote panel	Analogic